

Compact

Heterogeneous



Acczent Excellence 70

Budget solution with premium qualities.

With a 0.7 mm PVC wear layer, Acczent Excellence 70 ranges are competitively priced compact heterogeneous vinyl floorings with good resistance to indentation, abrasion and tearing.

A coordinated palette of colours and designs such as wood and mineral effects make this a good choice for for heavy traffic in sectors such as education, healthcare and retail.

The surface benefits from TOPCLEAN reinforcement which means no wax and no polish and good cleaning and maintenance properties.



Acczent Excellence 70


Topaz	P. 112-113
Ruby	P. 114-117
Opal	P. 118-119

Technical data		Acczent Excellence 70 Topaz	Acczent Excellence 70 Ruby	Acczent Excellence 70 Opal
Classification	ISO 10874 (EN 685) commercial industrial	Classes: 34 43	Classes: 34 43	Classes: 34 43
Polyurethane reinforcement (PUR)	—	TOPCLEAN	TOPCLEAN	TOPCLEAN
Total thickness	ISO 24346 (EN 428)	2.50 mm	2.00 mm	2.00 mm
Wear layer thickness	ISO 24340 (EN 429)	0.70 mm	0.70 mm	0.70 mm
Total weight	ISO 23997 (EN 430)	2 900 g/m²	3 000 g/m²	3 000 g/m²
Abrasion group	EN 660-2	Group T: ≤ 2 mm³	Group T: ≤ 2 mm³	Group T: ≤ 2 mm³
Residual indentation	ISO 24343-1 (EN 433)	≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm
Furniture leg	EN 424	No damage	No damage	No damage
Castor wheel test	ISO 4918 (EN 425)	No damage	No damage	No damage
Dimensional stability	ISO 23999 (EN 434)	≤ 0.10 %	≤ 0.10 %	≤ 0.10 %
Curl resultant to heat	ISO 23999 (EN 434)	≤ 8 mm	≤ 8 mm	≤ 8 mm
Reaction to fire	EN 13501-2	Cfl S1 glued over any A2fl or A1fl substrate (concrete) and over any derivative wood substrate	Bfl S1 glued over any A2fl or A1fl substrate (concrete) and over any derivative wood substrate	Bfl S1 glued over any A2fl or A1fl substrate (concrete) and over any derivative wood substrate
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3	R10 ≥ 0.3	R9 ≥ 0.3
Electrostatic properties	EN 1815 EN 1081	≤ 2 kV on concrete R1 > 10⁹ ohms	≤ 2 kV on concrete R1 > 10⁹ ohms	≤ 2 kV on concrete R1 > 10⁹ ohms
Light fastness	EN ISO 105-B02	≥ 6	≥ 6	≥ 6
Chemical resistance	ISO 26987 (EN 423)	High resistance	High resistance	High resistance
Hygiene	—	Does not contribute to infection spreading	Does not contribute to infection spreading	Does not contribute to infection spreading
Thermal resistance Underfloor heating	EN ISO 10456	0.02 m² K/W Suitable	0.02 m² K/W Suitable	0.02 m² K/W Suitable
Colours	—	Clic: 13 Wood: 11	Nature: 23 Wood: 13	Clic: 13 Wood: 4
Form of delivery	ISO 24341 (EN 426)	Rolls: 24 lm x 2 m Rolls: 24 lm x 3 m Rolls: 24 lm x 4 m	Rolls: 23 lm x 2 m Rolls: 23 lm x 4 m	Rolls: 23 lm x 2 m Rolls: 23 lm x 4 m


The above information is subject to modifications for the benefit of further improvement (01/2013).
For more detailed technical information, please contact Tarkett.

Acczent Excellence 70

Topaz



- Heavy traffic flooring ideal for all commercial areas
- High comfort flooring with outstanding hygiene performance
- Mineral pattern in soft colors and classic wood designs
- TopClean PUR surface treatment for easy, low cost maintenance



Wood

Clic




Wood



Soft Elm brown

- 2 m: 5626 001
- 3 m: 5625 001
- 4 m: 5624 001



Antik Oak light brown

- 2m: 5626 005
- 3m: 5625 005
- 4m: 5624 005



Beech light brown

- 2m: 5626 006
- 3m: 5625 006
- 4m: 5624 006



Beech beige yellow

- 2m: 5626 025
- 3m: 5625 025
- 4m: 5624 025



Antik Oak white

- 2m: 5626 026
- 3m: 5625 026
- 4m: 5624 026




Antik Oak light natural

- 2m: 5626 027
- 3m: 5625 027
- 4m: 5624 027



Soft Elm natural

- 2m: 5626 028
- 3m: 5625 028
- 4m: 5624 028



Arcadia middle natural

- 2m: 5626 029
- 3m: 5625 029
- 4m: 5624 029



Arcadia brown natural

- 2m: 5626 030
- 3m: 5625 030
- 4m: 5624 030



Arcadia light grege

- 2m: 5626 031
- 3m: 5625 031
- 4m: 5624 031



Arcadia light yellow

- 2m: 5626 032
- 3m: 5625 032
- 4m: 5624 032




Clic

- 2m: 5626 015
- 3m: 5625 015
- 4m: 5624 015



- 2m: 5626 016
- 3m: 5625 016
- 4m: 5624 016



- 2m: 5626 017
- 3m: 5625 017
- 4m: 5624 017



- 2m: 5626 018
- 3m: 5625 018
- 4m: 5624 018



- 2m: 5626 019
- 3m: 5625 019
- 4m: 5624 019




- 2m: 5626 020
- 3m: 5625 020
- 4m: 5624 020




- 2m: 5626 021
- 3m: 5625 021
- 4m: 5624 021




- 2m: 5626 022
- 3m: 5625 022
- 4m: 5624 022



- 2m: 5626 023
- 3m: 5625 023
- 4m: 5624 023



- 2m: 5626 024
- 3m: 5625 024
- 4m: 5624 024



- 2m: 5626 034
- 3m: 5625 034
- 4m: 5624 034



- 2m: 5626 035
- 3m: 5625 035
- 4m: 5624 035



- 2m: 5626 036
- 3m: 5625 036
- 4m: 5624 036

Acczent Excellence 70

Ruby

TARKETT BALANCED CHOICE	52%	100% 24%	 <100 µg/m³* Better Indoor Air Quality
	Natural	Recyclable Recycled content	

- 
- TopTM
Clean**
- PUR REINFORCED**
- NO WAX
NO POLISH**



Trend Oak white beige



Trend Oak natural brown



Oak grey/beige



Oak grey



Lower




Cherry dark




VINYL

Acczent Excellence 70

Opal



- Heavy traffic flooring ideal for all commercial areas
- Color combinations between all over designs and uni shade
- Excellent resistance to indentation and abrasion (0.7mm wear layer)
- TopClean PUR surface treatment for easy, low cost maintenance



Wood



2m: 3810 024
4m: 3811 024



2m: 3810 021
4m: 3811 021



2m: 3810 022
4m: 3811 022



2m: 3810 020
4m: 3811 020

Clic



2m: 3810 035
4m: 3811 035



2m: 3810 033
4m: 3811 033




2m: 3810 030
4m: 3811 030



2m: 3810 027
4m: 3811 027




2m: 3810 034
4m: 3811 034




2m: 3810 036
4m: 3811 036




2m: 3810 026
4m: 3811 026




2m: 3810 037
4m: 3811 037



2m: 3810 029
4m: 3811 029




2m: 3810 028
4m: 3811 028



2m: 3810 025
4m: 3811 025



2m: 3810 032
4m: 3811 032



2m: 3810 031
4m: 3811 031

