

Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: TREMCO CS175 A

· MSDS code: W-T-CS175A

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Epoxy resin

Primer / Subcoating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Coatings Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R36/38: Irritating to eyes and skin.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 1)

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS09

· Signal word Warning

· Contains:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700) 2,3-epoxypropyl neodecanoate

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

Wear protective gloves / eye protection. P280

P273 Avoid release to the environment.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Supplemental information:

Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy	30- <50%
NLP: 500-033-5	resin (number average molecular weight ≤ 700)	
Reg.nr.: 01-2119456619-26-xxxx	Xi R36/38; Xi R43; N R51/53	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
(Contd. on page 2		

(Contd. on page 3)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

	(Co	ntd. of page 2)
CAS: 26761-45-5	2,3-epoxypropyl neodecanoate	5- <10%
EINECS: 247-979-2	Xi R43; N R51/53	
Reg.nr.: 01-2119431597-33-xxxx	Aquatic Chronic 2, H411; Skin Sens. 1, H317	
CAS: 9016-45-9	nonoxinol	0.1- <1%
NLP: 500-024-6	Xi R36/38; N R51/53	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
· SVHC		
9016-45-9 nonoxinol		

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Irritating to eyes and skin.

- Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

- · 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

(Contd. on page 4)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

The usual precautionary measures are to be adhered to when handling chemicals.

Open and handle receptacle with care.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: The product is not flammable.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

· Information about storage in one common storage facility:

Protect from heat and direct sunlight.

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

Store away from reducing agents.

· Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep indoors.

Storage temperature: +10 ℃ to +35 ℃

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 4)

- 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

PVA gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: White

Odour: Characteristic

· Boiling point/Boiling range: 100 ℃

• Flash point: $> 100 \, ^{\circ}$

• **Danger of explosion:** Product does not present an explosion hazard.

Density at 20 ℃: 1.03 g/cm³

(Contd. on page 6)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 5)

· Solubility in / Miscibility with

water: Fully miscible.

· Viscosity:

Dynamic at 20 ℃: 2400 mPas

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:		
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
26761-45-5 2,3-epoxypropyl neodecanoate		
Oral	LD50	>9600 mg/kg (rat)

Oral LD50 >9600 mg/kg (rat) Dermal LD50 >3800 mg/kg (rabbit) Inhalative LC50/4 h 26 mg/L (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Causes serious eye irritation.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability The product is not easily, but potentially biodegradable.
- · 12.3 Bioaccumulative potential May be accumulated in organism
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 6)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

· Waste disposal key: UK: H4 H14

· European waste catalogue

08 01 15* aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	2002 ENVIDONMENTALLY HAZADDOUG
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700))
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700)), MARINE
· IATA	POLLUTANT ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700))
	(Contd. on page 8)

onia. on page o



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

4407	(Contd. of page 7)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
14.4 Packing groupADR, IMDG, IATA	Ш
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: bisphenol A epoxy resin (number average MW ≤700) Yes
Special marking (ADR):Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Danger code (Kemler):EMS Number:	90 F-A,S-F
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	x II of Not applicable.
· Transport/Additional information:	
ADRLimited quantities (LQ)Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
-	Maximum net quantity per outer packaging: 1000 ml
Transport categoryTunnel restriction code	3 E
	(Contd. on page 9)

- GB



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 8)

· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
· UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700)), 9, III	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC.

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

9016-45-9 nonoxinol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)



Printing date 05.08.2014 Version number 2 Revision: 05.08.2014

Trade name: TREMCO CS175 A

(Contd. of page 9)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· * Data compared to the previous version altered.