

Pos.	Masse	Gegenstand	Einheitspreis		Betrag	
			Euro		Euro	
1		<p><b>DAMTEC® resistant cork</b> Special insulating underlay for floors in residential and other buildings. With special selection of raw material of low flammability. It's suitable for parquetry and laminated floor as well as for textile floors.</p> <p><b>DAMTEC® resistant cork G</b> is grinded on one side and can be used for PVC and Linoleum flooring.</p> <p><i>Manufacturer:</i> Gummiwerk KRAIBURG RELASTEC GmbH Fuchsbergerstr.4, D-29410 Salzwedel, Tel. +49/8683-701 142, Fax +49/8683-701 4 142</p> <p><i>Material:</i> Granules of recycled rubber and cork with PU elastomer bonding agent</p> <p><i>Delivery:</i> rolls Thickness (<math>\pm 0.3\text{mm}</math>)/Width (<math>\pm 1.5\%</math>)/Length (<math>\pm 1.5\%</math>): 2mm/1,25m/30m, 3/1,25/20, 4/1,25/20, 5/1,25/15, 6/1,25/20 (other dimensions on request)</p> <p><i>Physical Characteristics:</i> tensile strength: 0.6 N/mm<sup>2</sup> (EN ISO 1798) elongation at break: approx. 10% (EN ISO 1798) density: approx. 600kg/m<sup>3</sup> flammability rating: C<sub>fl</sub>-s1 (EN 13501) service temperature range: - 30°C to + 80°C</p> <p><i>Properties:</i> resistance to moisture absorption and rot degradation, high compressive strength and load-bearing performance, for use with under floor heating</p> <p><i>Installation:</i> In accordance <b>DAMTEC® resistant cork (G)</b> installation instructions.</p> <p><i>(grinded, glued)</i> m<sup>2</sup> <b>DAMTEC® resistant cork G</b>, impact sound</p>				

Pos.	Masse	Gegenstand	Einheitspreis		Betrag	
			Euro		Euro	
1		<p>insulation made of recycled rubber granules, shrank in PE membrane, on pallets to be supplied and considering the manufacturer data stick down professionally on to even and stable underground with suitable adhesive after choice of the offerer. Adhesive, Type _____</p> <p>Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH Product: <b>DAMTEC® resistant cork G</b> Thickness: ____ mm</p> <p>Installation has to be in accordance with installation instructions of manufacturer.</p> <p><i>(grinded, loose laid)</i> m² <b>DAMTEC® resistant cork G</b>, impact sound insulation made of recycled rubber granules, shrank in PE membrane, on pallets to be supplied and installed.</p> <p>Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH Product: <b>DAMTEC® resistant cork G</b> Thickness: ____ mm</p> <p>Installation has to be in accordance with installation instructions of manufacturer.</p> <p><i>(not grinded, glued)</i> m² <b>DAMTEC® resistant cork</b>, impact sound insulation made of recycled rubber granules, shrank in PE membrane, on pallets to be supplied and considering the manufacturer data stick down professionally on to even and stable underground with suitable adhesive after choice of the offerer. Adhesive, Type _____</p> <p>Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH Product: <b>DAMTEC® resistant cork</b> Thickness: ____ mm</p> <p>Installation has to be in accordance with installation instructions of manufacturer.</p> <p><i>(not grinded, loose laid)</i> m² <b>DAMTEC® resistant cork</b>, impact sound insulation made of recycled rubber granules, shrank in PE membrane, on pallets to be supplied and installed.</p>				

Dieser Ausschreibungstext unterliegt keinem Änderungsdienst! Alle Angaben erfolgen ohne Gewähr.  
Die jeweils aktuelle, gültige Fassung ist abrufbar unter [www.kraiburg-relastec.de/sportec](http://www.kraiburg-relastec.de/sportec)

Seite 2 von 3

Pos.	Masse	Gegenstand	Einheitspreis		Betrag	
			Euro		Euro	
1		<p>Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH                      Product: <b>DAMTEC® resistant cork</b>                      Thickness: ____ mm</p> <p>Installation has to be in accordance with installation instructions of manufacturer.</p>				

**DISCLAIMER:**

Mit unseren Angaben wollen wir Sie aufgrund unserer Versuche und Erfahrungen nach bestem Wissen und Gewissen beraten. Eine Gewährleistung für das Verarbeitungsergebnis kann KRAIBURG RELASTEC im Einzelfall jedoch wegen der Vielzahl an Verwendungsmöglichkeiten und der außerhalb unseres Einflusses liegenden Lagerungs-, Verarbeitungs- und Baustellenbedingungen für seine DAMTEC® Produkte nicht übernehmen. Eigenversuche sind durchzuführen. Unser technischer Kundenservice steht Ihnen gerne zur Verfügung.

Dieser Ausschreibungstext unterliegt keinem Änderungsdienst! Alle Angaben erfolgen ohne Gewähr.

Die jeweils aktuelle, gültige Fassung ist abrufbar unter [www.kraiburg-relastec.de/damtec](http://www.kraiburg-relastec.de/damtec)