

Pos.	Masse	Gegenstand	Einheitspreis		Betrag	
			Euro		Euro	
1		DAMTEC® system the premium insulating padding for concrete or wooden subfloors. DAMTEC® system's special design and granular-textured surface ensure superior acoustic insulation especially in the low frequency range. <i>Manufacturer:</i> Gummiwerk KRAIBURG RELASTEC GmbH Fuchsbergerstr.4, D-29410 Salzwedel, Tel. +49/8683-701 142, Fax +49/8683-701 4 142 <i>Material:</i> Two-layer compound with rubber granules and rubber mat with PU elastomer bonding agent <i>Delivery:</i> Rolls Thickness (±0.3mm)/Width (±1.5%)/Length (±1.5%): approx. 6/1/10 <i>Physical Characteristics:</i> Area weight: approx. 3,1kg/m² service temperature range: - 30°C to + 80°C heat transmission coefficient: 0.07 m²K/W max. load: 0.05N/mm² impact sound improvement: (EN ISO 140-8) - 23dB one layer - 26dB two layer <i>Properties:</i> The floor underlay meets the demands of AgBB scheme and is suitable for the use in interiors of buildings. Resistance to moisture absorption and rot degradation, high compressive strength and load-bearing performance. For use with under floor heating. <i>Installation:</i> In accordance DAMTEC® system installation instructions. m² DAMTEC® system, impact sound insulation made of recycled rubber granules, shrunk in PE membrane,				

Pos.	Masse	Gegenstand	Einheitspreis		Betrag	
			Euro		Euro	
1		on pallets to be supplied and installed. Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH Product: DAMTEC® system Impact Sound Reduction: _____ dB Installation has to be in accordance with installation instructions of manufacturer. Rolls of duct tape (length: 50m) It is recommended to glue tape over the joints. (in acc. with manufacturer's recommendations). m² PE membrane Thickness: _____ mm After installation of insulating underlay cover it with suitable PE membrane (for example PE 0.2 mm). (in acc. with manufacturer's recommendations). rolls peripheral insulation strip: (length: 50m) height _____ mm thickness _____ mm. Install it over all structural components which extend upward or laterally such as walls, pipes etc. before installation of floor system components. (in accordance with manufacturer's recommendations). Materials: _____ Labour: _____				

DISCLAIMER:

Mit unseren Angaben wollen wir Sie aufgrund unserer Versuche und Erfahrungen nach bestem Wissen und Gewissen beraten. Eine Gewährleistung für das Verarbeitungsergebnis kann KRAIBURG RELASTEC im Einzelfall jedoch wegen der Vielzahl an Verwendungsmöglichkeiten und der außerhalb unseres Einflusses liegenden Lagerungs-, Verarbeitungs- und Baustellenbedingungen für seine DAMTEC® Produkte nicht übernehmen. Eigenversuche sind durchzuführen. Unser technischer Kundenservice steht Ihnen gerne zur Verfügung.

Dieser Ausschreibungstext unterliegt keinem Änderungsdienst! Alle Angaben erfolgen ohne Gewähr.
Die jeweils aktuelle, gültige Fassung ist abrufbar unter www.kraiburg-relastec.de/damtec

Dieser Ausschreibungstext unterliegt keinem Änderungsdienst! Alle Angaben erfolgen ohne Gewähr.
Die jeweils aktuelle, gültige Fassung ist abrufbar unter www.kraiburg-relastec.de/sportec

Seite 2 von 2