

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FR220 – 20160224


- 1. Unique identification code of the product-type:** FR220
- 2. Intended use/es:** Nullifire FR 220 FIRE STOPPING COMPOUND is a gypsum based mortar material, used to reinstate the fire performance of floor and wall constructions where they have been provided with apertures for the penetration of multiple services.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 used as EAD
European Technical Assessment: ETA 14/0337 of 03/09/2014
Technical Assessment Body: Warrington Certification Limited
Notified Body: 1121, Warrington Certification Limited

7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification
Safety in Case of Fire		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to E 240 and EI 180 Resistance to fire performance & field of application in accordance with EN13501-2 See ETA 14/0337 - Annex C	EN13501-2 EN1366-3: 2009
Hygiene, Health and Environment		
Dangerous Substances	Does not contain dangerous substances See ETA 14/0337 Clause 3.5	Declaration of Manufacturer
Energy, Economy and Heat Retention		
Service & Durability	Z ₁ intended for use in internal conditions with humidity ≥ 85% RH, temperatures 0/+40 °C, without exposure to rain or UV in accordance with EOTA Technical Report TR024: 2009	ETAG 026-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
M. Liptrot, Business Unit Director Sealants & Coatings
At Wigan on 24 February 2016



Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FR220 – 20160224

CE	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 1121-CPR-JA5041 FR220 – 20160224 www.nullifire.com/FR220/	
EN 1366-3: 2009 14/0337 ETAG 26, Part 1 ETAG 26, Part 2	
Nullifire FR 220 FIRE STOPPING COMPOUND is a gypsum based mortar material, used to reinstate the fire performance of floor and wall constructions where they have been provided with apertures for the penetration of multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class F
Resistance to fire	Up to E 240 and EI 180 Resistance to fire performance & field of application in accordance with EN13501-2 See ETA 14/0337 - Annex C
Hygiene, Health and Environment	
Dangerous Substances	Does not contain dangerous substances See ETA 14/0337 Clause 3.5
Energy, Economy and Heat Retention	
Service & Durability	Z ₁ intended for use in internal conditions with humidity ≥ 85% RH, temperatures 0/+40 °C, without exposure to rain or UV in accordance with EOTA Technical Report TR024: 2009
Other	NPD