

## DECLARATION OF PERFORMANCE (DoP: HFR-002)

### Construction Products Regulation (EU) No 305/2011



**Product type:** HERTALAN® EASY COVER FR, ≥ 1,2 MM

**Type, batch or serial number:** See product or packaging

**Intended Use:** Flat roof waterproofing, EN 13956

**Contact data producer:** Carlisle Construction Materials BV  
Industrieweg 16  
NL-8263 AD KAMPEN

**AVCP:** 2+

**Notified body (hEN):** KIWA n.v., Sir W. Churchillaan 273, NL-2288 EA Rijswijk  
Notified body no.: 0620  
FPC: 0620-CPR-44520

#### Declared performance:

Essential characteristics	Performance	Test standard	Harmonised technical standard
External fire performance	Roof	EN 13501-5	EN 13956: 2013
Reaction to fire	Class E	EN 13501-1	
Water tightness	Pass	EN 1928	
Tensile strength (l/t) (N/mm <sup>2</sup> )	≥ 8	EN 12311-2B	
Elongation (l/t) (%)	≥ 400	EN 12311-2B	
Resistance to root penetration	Pass	EN 13948	
Resistance to static load (kg)	≥ 25	EN 12730	
Resistance to impact (mm)	≥ 300	EN 12691	
Tear resistance (l/t) (N)	≥ 25	EN 12310-2	
Joint peel resistance (N/50mm)	≥ 50	EN 12316-2	
Joint shear resistance (N/50mm)	≥ 200	EN 12317-2	
Foldability at low temperature (°C)	≤ -45	EN 495-5	
UV exposure (1.000 h)	Pass	EN 1297	
Dangerous substances	Meets requirements		

#### Declaration

The performance of the product is in conformity with the declared performance. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Bart Smit, R&D manager

Kampen, February 2017

