

Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: Nullifire SC902 B

· MSDS code: W-N-SC902B

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against -
- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

tremco illbruck Coatings Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

Nullifire

Torrington Avenue, Coventry, CV4 9TJ

T: +44 (0) 2476855000, F: +44 (0) 2476469547

www.nullifire.com, protect@nullifire.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 2476855000. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R36: Irritating to eyes.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Contains:

3-(trimethoxysilyl)propylamine

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

- 2.3 Other hazards No further relevant information available.
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 1330-20-7	xylene (mix)	5- <10%
EINECS: 215-535-7	Xn R20/21; Xi R38	
Reg.nr.: 01-2119488216-32-xxxx	R10	
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 13822-56-5	3-(trimethoxysilyl)propylamine	5- <10%
EINECS: 237-511-5	Xi R38-41	
Reg.nr.: 01-2119510159-45-xxxx	Eye Dam. 1, H318; Skin Irrit. 2, H315	
CAS: 100-41-4	ethylbenzene	1- <5%
EINECS: 202-849-4	Xn R20; F R11	
Reg.nr.: 01-2119489370-35-xxxx	Flam. Liq. 2, H225; Acute Tox. 4, H332	

· Additional information:

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Methanol (CAS 67-56-1)

For the wording of the listed risk phrases refer to section 16.

- GE



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Irritant to skin and mucous membranes.

Risk of serious damage to eyes.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- GE



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Provide ventilation for receptacles.

- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: +5 ℃ to +25 ℃

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

· Ingredients with biological limit values:

1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· Additional information:

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Do not breathe spray.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 4)

· Respiratory protection:

Use only in well-ventilated areas.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Viscous

Colour: According to product specification

· Odour: Characteristic

· Boiling point/Boiling range: > 100 ℃

· Flash point: 51 $^{\circ}$

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Density at 20 ℃: 1 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

(Contd. on page 6)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 5)

Solvent content:

VOC (EC) 112 g/l

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

methanol

Nitrogen oxides

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

^_^		£ I	! . !
 CALL VALUE	: raiavant	TOP C	lassification:
JJU values	, i CiC valit	101 6	iassiiivatioii.

1330-20-7 xylene (mix)

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Risk of serious damage to eyes.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

1330-20-7 xylene (mix)

EC50/48 h 7.4 mg/L (daphnia magna)

EC50/72 h | 10 mg/L (skelettonema costatum)

LC50/96 h | 3.77 mg/L (fish)

• 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

(Contd. of page 6)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Overall evaluation

Avoid transfer into the environment.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Waste disposal key: UK: H3B
- · European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14	: Transport	information
------------	-------------	-------------

Void
Void
Void
Void
No
Not applicable.
of Not applicable.

(Contd. on page 8)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

		(Contd. of page 7)
· Transport/Additional information:		
· ADR	2.2.3.1.1 (note 1) 2.2.3.1.5	
· IMDG	2.3.1.2 + 2.3.1.3 2.3.2.5	
· IATA	3.3.1.2 + 3.3.1.3	
· UN "Model Regulation":	UN-, -	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC.

- "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).
- "CHIP" SI 2009 No.716.
- "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



Printing date 14.05.2015 Version number 5 Revision: 14.05.2015

Trade name: Nullifire SC902 B

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 · * Data compared to the previous version altered.

(Contd. of page 8)