



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: TREMCO SF600 B

· MSDS code: W-T-SF600B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Adhesives

Additional component

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Coatings Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-40-48/20: Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of

serious damage to health by prolonged exposure through inhalation.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

(Contd. on page 2)



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Contains:

diphenylmethanediisocyanate, isomers and homologues

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P280 Wear protective gloves / eye protection.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing vapours.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Supplemental information:

Contains isocyanates. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

	(C	onta. or page 2)		
· Dangerous components:				
CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues	75- <100%		
EINECS: 202-966-0	Xn R20-40-48/20; Xn R42/43; Xi R36/37/38			
	Carc. Cat. 3			
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute			
	Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,			
	H317; STOT SE 3, H335			

· Additional information:

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Carbon dioxide

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Breathing difficulty

Irritating to eyes, respiratory system and skin.

May cause damage to organs through prolonged or repeated exposure.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

GB



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

Nitrogen oxides (NOx)

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information Do not allow water to get inside the containers.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation

Remove persons from danger area.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not seal receptacles gas-tight.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: The product is not flammable.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- · Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Store in a cool place.

Store in dry conditions.

Protect from humidity and water.

· 7.3 Specific end use(s) No further relevant information available.

- GE



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen: as -NCO

· Additional information:

The lists valid during the making were used as basis. EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not breathe vapour.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use only in well-ventilated areas.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended thickness of the material: ≥ 0.02 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

(Contd. of page 5)

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Brown
Colour: Brown
Odour: Rotten
Melting point/Melting range: $41 \, ^{\circ}\mathbb{C}$ Boiling point/Boiling range: $> 200 \, ^{\circ}\mathbb{C}$

• Flash point: $> 100 \, ^{\circ}$

· Ignition temperature: 530 ℃

• **Danger of explosion:** Product does not present an explosion hazard.

· Vapour pressure at 25 ℃: < 0.00001 hPa

• **Density at 20 ℃:** 1.24 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Danger of bursting.

Reacts with strong acids.

· 10.4 Conditions to avoid

Water / moisture.

Keep away from heat.

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:				
9016-87-9 diphenylmethanediisocyanate, isomers and homologues				
Oral	LD50	> 10000 mg/kg (rat)		
Dermal	LD50	> 10000 mg/kg (rabbit)		
Inhalative	LC50/4 h	0.493 mg/L (rat)	- (0	

(Contd. on page 7)



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

(Contd. of page 6)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eve: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc. 2

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
EC50/24 h	> 1000 mg/L (daphnia magna)	
LC0/96 h	> 1000 mg/L (brachydanio rerio)	
NOEC/21 d	> 10 mg/L (daphnia magna)	

- · 12.2 Persistence and degradability Not easily biodegradable
- 12.3 Bioaccumulative potential Not worth-mentioning accumulating in organisms
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Cured material may be disposed of as non-hazardous industrial waste.

· Waste disposal key: UK: H4 H5 H7

· European waste catalogue

08 05 01* waste isocyanates

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 8)





Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

Non contaminated packagings may be recycled.

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards:Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
 14.7 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	of Not applicable.
· UN "Model Regulation":	-

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC.

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

- National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 9)



Printing date 24.07.2014 Version number 2 Revision: 24.07.2014

Trade name: TREMCO SF600 B

			(Contd. of page 8)
H3	19 C	Causes serious eye irritation.	, , ,
H3:	32 H	farmful if inhaled.	
H3:	34 N	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H3:	35 N	May cause respiratory irritation.	
H3	51 S	Suspected of causing cancer.	
H3 ⁻	73 N	May cause damage to organs through prolonged or repeated exposure.	
R20	0 -	larmful by inhalation.	
R3	6/37/38 Ir	rritating to eyes, respiratory system and skin.	
R40	0 L	imited evidence of a carcinogenic effect.	
R4:	2/43 N	May cause sensitisation by inhalation and skin contact.	
R48	8/20 H	farmful: danger of serious damage to health by prolonged exposure through	h inhalation.
· Ab	breviatio	ons and acronyms:	

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

· * Data compared to the previous version altered.