

RENOLIT ALKORPLUS

INFORMATION SHEET

RENOLIT ALKORPLUS STAINLESS STEEL OUTLETS


A range of RENOLIT ALKORPLUS acid-free, stainless steel outlets is now available. The pipe is mounted onto a steel plate which may be secured through to the substrate. A sheet of RENOLIT ALKORPLAN foil is bonded to the steel pipe to comprise an integral unit.

The pipe is inserted into the outlet of the down pipe, the RENOLIT ALKORPLAN is heat welded to the roof sheet. This makes a completely watertight seal and preserves the integrity of the roof.




VERTICAL OUTLETS

	Diameter	Pipe Length	Flow Rate
	75 mm	400 mm	2.8 L/s
	110 mm	400 mm	4.2 L/s
	145 mm	400 mm	9.4 L/s


HORIZONTAL OUTLETS

	Horizontal Outlets	Diameter	Pipe Length	Flow rate
	95 x 95 mm	110 mm	400 mm	1.1 L/s

LEAF GUARDS

Horizontal Leaf guard	Wire Leaf Guard	Universal Leaf Grate
		

STAINLESS STEEL CABLE FLASHING

	The RENOLIT cable flashing (ø50) offers the ideal solution where cables must be brought through the roofing membrane for example solar systems or other electrical installations.
-------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

WWW.RENOLIT.COM/ROOFING



Rely on it.

RENOLIT Cramlington Ltd - Station Road, Cramlington, Northumberland NE23 8AQ - United Kingdom
T +44 1670 718283 - F +44 1670 590096 - renolit.cramlington@renolit.com