



Never compromise on quality!

Published: July 2008

# ECO XTREME

## Premium Environmental Gap-filling Adhesive

### Description

*An environmentally friendly, advanced technology formula offering instant grab and tough permanent bond on virtually any porous or non-porous surfaces.*

ECO XTREME is a low odour, >99% VOC free, water clean-up construction adhesive. Cures to form a high strength bond. Contains no harmful raw materials, making it safe for the environment, safe for the user and safe on substrates.

### Uses

ECO XTREME is ideal for adhering panelling, plasterboard, cove base, window sills, styrofoam, carpet tack strips, aluminium furring strips, tub surrounds, fireplaces, loose floor/wall tiles, plywood, aluminium, steel, wood, concrete, cork, general repairs to wood, fixing hardboard and plywood and as a general adhesive.

It is ideal for use on:

- ◆ plastics
- ◆ wood
- ◆ concrete
- ◆ brick
- ◆ plasterboard
- ◆ carpet
- ◆ metal

### Preparation

Ensure all surfaces to be bonded are clean, dry and free from grease or any contaminants that may hinder adhesion.

### Application

Cut tip off cartridge. Cut nozzle to required width of bead at a 45° angle. Place cartridge in a standard cartridge gun and apply as required. Once applied, surfaces should be firmly pressed together to aid bonding. If heavy panels are being bonded, temporary mechanical support may be necessary for 24 hours.

### Limitations

This adhesive should not be applied to building materials that bleed oils, plasticisers or solvents.

### Container Size

350ml plastic cartridge.

### Shelf Life

12 months.

### Storage Conditions

Store in cool, dry conditions. Do not allow to freeze.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

- ◆ Avoid eye contact.
- ◆ Avoid prolonged contact with skin.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

## Specification Summary

Flammability	Non flammable
Application Temperature	2°C to 60°C
Service Temperature	-40°C to + 82°C
Consistency	Thick paste - gun grade
Slump	None
Shrinkage	Approx 16%
Staining	None
Tack Free Time	5 minutes @ 20°C
Water Resistance	Good when fully cured
Bond Strength	>100KN/m <sup>2</sup> when fully cured
Coverage	6mm bead - 10 linear metres

### Container Sizes:

<b>Code:</b>	BDEX350
<b>Size:</b>	350ml

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.*