

SAFETY DATA SHEET


according to 1907/2006/EC, Article 31

LX 16 WOOD ADHESIVE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	LX 16 WOOD ADHESIVE
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Description	Adhesive.
1.3. Details of the supplier of the safety data sheet	
Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk
1.4. Emergency telephone number	
Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.1. Classification - 1999/45/EC	F; R11
Main hazards	Symbols: F: Highly flammable. Highly flammable.
2.2. Label elements	
Symbols	The product is classified in accordance with 67/548/EEC. F: Highly flammable. 
Risk phrases	R11 - Highly flammable.
Safety phrases	S1/2 - Keep locked up and out of the reach of children. S13 - Keep away from food, drink and animal feedingstuffs. S16 - Keep away from sources of ignition - No smoking. S46 - If swallowed, seek medical advice immediately and show this container or label.
2.3. Other hazards	
Other hazards	No data is available on this product.

LX 16 WOOD ADHESIVE

Revision 1

Revision date 2012-11-30

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Ethanol	603-002-00-5	64-17-5	200-578-6			F; R11
Acetone	606-001-00-8	67-64-1	200-662-2			F; R11 Xi; R36 R66 R67

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

General information

	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
--	---

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Alcohol resistant foam. Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Highly flammable. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	See section 8. PPE, 13. Disposal considerations for further information.
--	--

SECTION 7: Handling and storage

LX 16 WOOD ADHESIVE

Revision 1

Revision date 2012-11-30

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Acetone	WEL 8-hr limit ppm: 500	WEL 8-hr limit mg/m3: 1210
	WEL 15 min limit ppm: 1500	WEL 15 min limit mg/m3: 3620
Ethanol	WEL 8-hr limit ppm: 1000	WEL 8-hr limit mg/m3: 1920
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Brown
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Boiling point	56 °C
Flash point	-1 °C
Evaporation rate	No data available
Flammability limits	No data available
Vapour Flammability	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	1.49 (Water = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive	No data available
Oxidising	No data available
Solubility	Insoluble in water

9.2. Other information

LX 16 WOOD ADHESIVE

Revision 1

Revision date 2012-11-30

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data is available on this product.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

10.5. Incompatible materials

No data is available on this product.

10.6. Hazardous decomposition products

No data is available on this product.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1133

14.2. UN proper shipping name

ADHESIVES

14.3. Transport hazard class(es)

ADR/RID

3

Subsidiary risk

-

LX 16 WOOD ADHESIVE

Revision 1

Revision date 2012-11-30

14.3. Transport hazard class(es)

IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

14.6. Special precautions for user

	No data is available on this product.
--	---------------------------------------

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	No data is available on this product.
--	---------------------------------------

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220L
Packing Instruction (Passenger)	355
Maximum quantity	60L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
-------------	---

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 9 - 9.1. Information on basic physical and chemical properties (Flash point).
Text of risk phrases in Section 3	R11 - Highly flammable. R36 - Irritating to eyes. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--