



# SAFETRED TRANSPORT




Shale

3794 805




Battleship

3794 810




Sepia

3794 820



Riviera

3794 845




Cobalt

3794 850




Quasar

3793 100



Mercury

3793 180



Constellation


3793 190

TECHNICAL DATA	STANDARDS	Safetred Transport
<b>Classification</b>		
Type of floor covering	EN 13845	Heterogeneous safety floorings
Classification	Non applicable	Non applicable
<b>Characteristics</b>		
Total thickness	ISO 24346 (EN 428)	2.35mm
Total weight	ISO 23997 (EN 430)	3 300g/m <sup>2</sup>
Safety Clean XP™ PUR reinforcement	—	Yes
<b>Technical performances</b>		
Abrasion	EN 13845 Annex D	≤10% particle loss after 50,000 cycles
Residual indentation	ISO 24343-1 (EN 433) requirement	≤ 0.10mm
Dimensional stability	ISO 23999 (EN 434)	≤ 0.40%
Curl resistance to heat	ISO 23999 (EN 434)	≤ 2mm
Flame and smoke	ISO 3795 95/28/CEE FMVSS 302 Materials used in vehicles interior UTAC ST 18502-1	Test in progress
Slip resistance	TRRL Pendulum 4S (wet) BS 7976 part 2 DIN 51130 Surface Roughness Rz	> 36 R10 Esf > 20µm
Impact sound reduction	EN ISO 140-8 EN ISO 717/2 NFS 31-074 L <sub>n,e,w</sub>	ΔL <sub>w</sub> = 11dB 70dB
Light fastness	EN ISO 105-B02	7
Chemical resistance	ISO 26987 (EN 423)	Good resistance to everyday substances
Hygiene	—	Does not contribute to infection spreading

The above information is subject to modifications for the benefit of further improvement (07/2015).  
For more detailed technical information, please contact Tarkett.



Solar

 3793 260

## SAFETRED TRANSPORT

### Main Product Features

- High level of slip resistance
- Sustainable slip resistance throughout the product life
- Fleece backing for improved adhesion bond
- Hardwearing and durable for demanding environments
- Safety Clean XP™ PUR reinforced surface

### Surface Treatment



### Sustainability Tag



(1) For all products produced in 2015

### Logistics Information



Available in rolls  
Rolls length: 15lm

Laying direction:



Play with the Room Designer