

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

SILICONE RELEASE SPRAY CLP



Revision 1

Revision date 2015-05-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	SILICONE RELEASE SPRAY CLP
1.3. Details of the supplier of the safety data sheet	
Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk
1.4. Emergency telephone number	
Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.1. Classification - 67/548/EEC	F+; R12 Xi; R38 R52/53-67 Symbols: F+: Extremely flammable. Xi: Irritant.
Main hazards	Extremely flammable. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Aerosol 1: H222; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 3: H412;
2.2. Label elements	
Hazard pictograms	 
Signal Word	Danger
Hazard Statement	Aerosols 1: H222 - Extremely flammable aerosol. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

SILICONE RELEASE SPRAY CLP

Revision 1

Revision date 2015-05-20

2.2. Label elements

Precautionary Statement: Response	P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P235 - Store in a well-ventilated place. Keep cool.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butane	601-004-00-0	106-97-8	203-448-7			F+, R12	
Propane	601-003-00-5	74-98-6	200-827-9			F+, R12	
aliphatic hydrocarbon.		64742-49-0	265-151-9			F; R11 Xn; R65 Xi; R38 N; R51/53 R67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butane	601-004-00-0	106-97-8	203-448-7			Flam. Gas 1: H220;	
Propane	601-003-00-5	74-98-6	200-827-9			Flam. Gas 1: H220;	
aliphatic hydrocarbon.		64742-49-0	265-151-9			Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Irritating to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

SILICONE RELEASE SPRAY CLP

Revision 1

Revision date 2015-05-20

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Butane	WEL 8-hr limit ppm:	600	WEL 8-hr limit mg/m3:	1450
	WEL 15 min limit ppm:	750	WEL 15 min limit mg/m3:	1810
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	inhalable dust:		inhalable dust:	
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	respirable dust:		respirable dust:	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection -

Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

SILICONE RELEASE SPRAY CLP

Revision 1

Revision date 2015-05-20

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Clear
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	-40 °C
Flammability (solid, gas)	No data available
Autoignition temperature	Not applicable.
Explosive properties	No data available
Vapour pressure	No data available
Relative density	0.64 (H ₂ O = 1 @ 20 °C)
Partition coefficient	No data available
Viscosity	No data available
Vapour density	No data available
Evaporation rate	No data available
Fat Solubility	No data available
Oxidising properties	No data available
Solubility	Insoluble in water

9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

12.3. Bioaccumulative potential

--	--

Partition coefficient

	SILICONE RELEASE SPRAY No data available CLP
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SILICONE RELEASE SPRAY CLP

Revision 1

Revision date 2015-05-20

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

14.4. Packing group

Packing group -

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	-
Tunnel Category	(D)

IMDG

EmS Code F-D S-U

IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
-------------	---

SECTION 16: Other information

Other information

Revision This document differs from the previous version in the following areas:.

SILICONE RELEASE SPRAY CLP

Revision 1

Revision date 2015-05-20

Other information

	<p>2 - Precautionary Statement: Disposal. 11 - 11.1.4. Toxicological Information. 12 - 12.1. Toxicity. 14 - ADR/RID. 14 - IMDG. 14 - IATA. 15 - Regulations.</p>
Text of risk phrases in Section 3	<p>R11 - Highly flammable. R12 - Extremely flammable. R38 - Irritating to skin. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>Flam. Gas 1: H220 - Extremely flammable gas. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p>
Further information	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>