



Never compromise on quality!

FLOORING RANGE

FLOORBOND TS550

Polymer Wood Floor Adhesive

Description

TS550 is a permanently flexible, one part, ready to use, moisture cure, internal wood flooring adhesive. Free from silicone, solvent, isocyanates and water. Based on hybrid polymer technology; TS550 reduces the risk of warping or deforming the wood flooring due to its moisture and solvent free composition.

- Solvent and Moisture Free
- Quick Cure and Rapid Bond Strength
- Permanently Elastic
- Suitable for use with Underfloor Heating

Uses

For the internal bonding of parquet, mosaic, oak, wood block, laminated, exotic timber and many other wood floor types to porous or non porous substrates including; screeds, chipboard, plywood, concrete and anhydrite. **TS550** is also compatible with substrates incorporating under-floor heating systems.

Preparation

All surfaces must clean, dry and free from, grease, polish, old adhesive remnants or any other contaminants that may hinder adhesion. Loose, friable or cracked areas should be repaired prior to application. The moisture content throughout the substrate should be checked by Hygrometer, ensuring that the moisture content does not exceed that recommended by the wood flooring manufacturer for the particular substrate. In particular Anhydrite levels would differ to those of concrete. The wood flooring should also be checked that the relative humidity figure falls within those recommended by the manufacturer. Note; underfloor heating systems should be turned off 48 hours before and 48 hours after application.

Application

The application temperature should not be below +10°C and not above +30°C, materials should be acclimatised to this temperature in the intended application site prior to installation. Solid floors should have an existing DPM in place. Using a suitably sized notched trowel, apply the adhesive to the substrate. Do not apply more adhesive than will be used within 20 minutes of application. To ensure maximum transfer of adhesive to the wood, lay into the adhesive with a slight twisting motion and tap into place. Loading the

flooring with weights will ensure the 80% minimum coverage required is achieved and will improve the final bond strength.

TS550 will take at least 24 hours to cure assuming a temperature of 23C at 50% RH. Cooler and / or less humid conditions will extend drying times. Wait until the adhesive has fully cured before sanding or finishing the flooring.

Cleaning

Uncured **TS550** can be removed by white spirit. Cured adhesive must be removed mechanically.

Storage Conditions

Keep in cool, dry well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

Shelf Life

9 months when stored in original, unopened containers in cool dry conditions between +5°C and +20°C.

Coverage

Depending upon substrate condition and porosity the approximate coverage rates will be.

21m² with a B3 trowel.

15m² with a B13 trowel

Size

10 Litres.

Health & Safety

Avoid contact with eyes. Should contact occur, wash with plenty water for 15 minutes. Seek medical attention if symptoms persist. Avoid contact with skin. Should contact occur, wash with soapy water. Wear protective clothing, gloves and glasses. Ensure adequate ventilation of the working area. Safety Data Sheet available for the professional user upon request.

Note: as all surfaces differ; it is recommended that this product is tested on a small inconspicuous area to determine suitability before use. It is the users' responsibility to determine suitability.

Specification Summary

Density	1.49g/cc
Open Time	20 minutes
Shore A Hardness	40+/- 5
Tensile Strength	2.0 N/mm ²

Code:	BDTS55
Size:	10L
Barcode:	5060021368973

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V1 15/10/12