

## Specification


Modular vinyl floorcovering, with glass fibre reinforcement. TopClean XP™ polyurethane reinforcement. In plank and tile form.  
Product standard: ISO 10582.

CERTIFICATION & CLASSIFICATION	STANDARDS	iD Selection 40
Type of floor covering	EN ISO 10582	Compact Resilient Floorcovering
CE certification	EN 14041	Yes
Classification	EN ISO 10874	Domestic: 23 Commercial: 32 Industrial: 41
TECHNICAL CHARACTERISTICS	STANDARDS	iD Selection 40
Tota thickness	EN ISO 24346	2.2
Wear layer thickness	EN ISO 24340	0.4
Surface treatment (PUR)	-	Yes - TopCleanXP™
Beveled edges	-	No
Total weight	EN ISO 23997	3650 g/m <sup>2</sup>
Wear layer binder content	ISO 10582	Type I
Form of delivery	EN ISO 24342	
	Planks	16,66 x 100 cm, 27 planks/box = 4,50 m <sup>2</sup> 20 x 122 cm, 18 planks/box = 4,39 m <sup>2</sup> 25 x 122 cm, 14 planks/box = 4,27 m <sup>2</sup>
	Tiles	50 x 50 cm, 18 tiles/box = 4,50 m <sup>2</sup> 30,5 x 61 cm, 23 tiles/box = 4,28 m <sup>2</sup> 61 x 61 cm, 11 tiles/box = 4,09 m <sup>2</sup>
TECHNICAL PERFORMANCES	STANDARDS	iD Selection 40
Dimensional stability	EN ISO 23999	≤ 0,10 %
Reaction to fire	EN 13501-1	Bfl-s1 glued over concrete substrate Cfl-s1 glued over wood substrate
Residual indentation	EN ISO 24343-1	≤ 0,05 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Underfloor heating	-	Suitable - max. 27 °C
Thermal resistance	ISO 10456	0,02 m <sup>2</sup> K/W
Impact sound reduction	EN ISO 717-2	2 dB
Reduction of in room impact noise	NF EN ISO 31-074	Class C (Ln,e,w < 85 dB)
Light fastness	EN ISO 105-B02 Method 3	≥ 6
Resistance to chemicals	EN ISO 26987	High resistance
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0,30
Electrical properties	EN 1815 EN 1081	<2 kV on concrete ≥ 10 <sup>9</sup> Ohm
Colours		30

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF: 482050000000F



According to European Classification  
ISO 10874 - EN 685

