

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	FILL 'N' FIX FOAM CLP
--------------	-----------------------

1.3. Details of the supplier of the safety data sheet

Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk

1.4. Emergency telephone number


Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	F+; R12 Xn; R20-40-42/43-48/20 Xi; R36/37/38 N; R50/53 R64-66 Symbols: F+: Extremely flammable. Xn: Harmful. N: Dangerous for the environment.
Main hazards	Extremely flammable. Harmful by inhalation. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies. Repeated exposure may cause skin dryness or cracking.
2.1.2. Classification - EC 1272/2008	EUH066; Aerosols 1: H222; Flam. Liq. 2: H225; Aerosol 1, 2, 3: H229; Acute Tox. 4: H302+H332; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; Lact.: H362; STOT RE 2: H373; Aquatic Chronic 1: H410;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking. Aerosols 1: H222 - Extremely flammable aerosol. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Aerosols, 1, 2, 3: H229 - Pressurised container: May burst if heated. Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

2.2. Label elements

	<p>Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Carc. 2: H351 - Suspected of causing cancer . Lact.: H362 - May cause harm to breast-fed children. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>
Precautionary Statement: Prevention	<p>P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P251 - Do not pierce or burn, even after use. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P263 - Avoid contact during pregnancy/while nursing. P264 - Wash thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - [In case of inadequate ventilation] wear respiratory protection.</p>
Precautionary Statement: Response	<p>P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell. P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P330 - Rinse mouth. P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/ . P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F. P410 - Protect from sunlight. P412 - Do not expose to temperatures exceeding 50°C/ 122°F.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations</p>

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

SECTION 3: Composition/information on ingredients**3.1. Substances****67/548/EEC / 1999/45/EC**

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
alkanes, C14-17, chloro - Aerosol		85535-85-9			30 - 40%	N; R50/53 R64-66	
Diphenylmethanediisocyanate, isomers and homologues		9016-87-9			10 - 20%	Xn; R20-40-42/43-48/20 Xi; R36/37/38	
Propane-1,2-diol, propoxylated		25322-69-4			1 - 10%	Xn; R22	
Dimethyl ether	603-019-00-8	115-10-6	204-065-8		1 - 10%	F+; R12	
Isobutane	601-004-00-0	75-28-5	200-857-2		1 - 10%	F+; R12	
Propane	601-003-00-5	74-98-6	200-827-9		0.5 - 1%	F+; R12	
Butane	601-004-00-0	106-97-8	203-448-7		0.5 - 1%	F+; R12	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
alkanes, C14-17, chloro - Aerosol		85535-85-9				Lact.: H362; Aquatic Chronic 1: H410; EUH066;	
Diphenylmethanediisocyanate, isomers and homologues		9016-87-9				Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Acute Tox. 4: H332; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; STOT RE 2: H373;	
Propane-1,2-diol, propoxylated		25322-69-4					
Dimethyl ether	603-019-00-8	115-10-6	204-065-8			Flam. Gas 1: H220;	
Isobutane	601-004-00-0	75-28-5	200-857-2			Flam. Gas 1: H220;	
Propane	601-003-00-5	74-98-6	200-827-9			Flam. Gas 1: H220;	
Butane	601-004-00-0	106-97-8	203-448-7			Flam. Gas 1: H220;	

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Irritating to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Butane	WEL 8-hr limit ppm:	600	WEL 8-hr limit mg/m3:	1450
	WEL 15 min limit ppm:	750	WEL 15 min limit mg/m3:	1810
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-
Dimethyl ether	WEL 8-hr limit ppm:	400	WEL 8-hr limit mg/m3:	766
	WEL 15 min limit ppm:	500	WEL 15 min limit mg/m3:	958
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection -
Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear suitable respiratory equipment when necessary.

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Aerosol
Colour	Yellow
Odour	Characteristic
Flash point	-20 °C
Relative density	1.1 (H ₂ O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Odour threshold	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Solubility	Insoluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	No data available

SECTION 10: Stability and reactivity**10.2. Chemical stability**

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information**11.1.4. Toxicological Information**

	No data available
--	-------------------

SECTION 12: Ecological information**12.1. Toxicity**

	No data available
--	-------------------

12.3. Bioaccumulative potential

--	--

Partition coefficient

--	--

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

Partition coefficient

FILL 'N' FIX FOAM CLP No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID

2

Subsidiary risk

see SP63

IMDG

2

Subsidiary risk

see SP63

IATA

2

Subsidiary risk

see SP63

14.4. Packing group

Packing group

-

14.5. Environmental hazards

Environmental hazards

Yes

Marine pollutant

Yes

ADR/RID

Hazard ID

-

Tunnel Category

(D)

IMDG

EmS Code

F-D S-U

IATA

Packing Instruction (Cargo)

203

Maximum quantity

150 kg

Packing Instruction (Passenger)

203

Maximum quantity

75 kg

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending

FILL 'N' FIX FOAM CLP

Revision 0

Revision date 2015-05-21

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.

SECTION 16: Other information**Other information****Text of risk phrases in Section 3**

R12 - Extremely flammable.
 R20 - Harmful by inhalation.
 R22 - Harmful if swallowed.
 R36/37/38 - Irritating to eyes, respiratory system and skin.
 R40 - Limited evidence of a carcinogenic effect.
 R42/43 - May cause sensitisation by inhalation and skin contact.
 R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R64 - May cause harm to breastfed babies.
 R66 - Repeated exposure may cause skin dryness or cracking.

Text of Hazard Statements in Section 3

Skin Irrit. 2: H315 - Causes skin irritation.
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Acute Tox. 4: H332 - Harmful if inhaled.
 Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 STOT SE 3: H335 - May cause respiratory irritation.
 Carc. 2: H351 - Suspected of causing cancer .
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
 Flam. Gas 1: H220 - Extremely flammable gas.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.