

Declaration of Performance
VBP/CPR/DPM002



Visqueen Building Products
Heanor Gate Industrial Estate
Derbyshire UK, DE75 7RG

Declares that the products stated below conform to:

Annex ZA of EN 13967: Flexible sheets for waterproofing

0836-CPD – 13/F029

Products

Visqueen Ecomembrane (BBA product ranges 0.25, 0.3 and 0.5mm)

Product Type

Type A in accordance to EN 13967

System of assessment of verification of constancy of performance (AVCP)

System 2+

Use

Plastic or rubber sheet used on or under floors/ground slabs or in walls to prevent liquid water not under hydrostatic pressure passing from the ground into the internal environment.

Compliance

British Board of Agreement performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control. 0836-CPD – 13/F029 applies.

Declaration of Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	F	EN 13967
Water tightness	Pass	
Resistance to Impact	30mm	
Resistance to static loading	20Kg	
Durability against heat ageing	Pass	
Durability against chemicals	Pass	

Place

Signature

Date

Derbyshire, UK

17/05/2013

Cameron Yates
Product Manager