

DECLARATION OF PERFORMANCE

DOP-8327AD-01

1. Unique identification code of the product-type:
8327AD
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
8327AD
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Application: Plastic and rubber vapour control layers EN 13984
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
DuPont de Nemours (Luxembourg) S.à r.l.
Rue General Patton, L-2984 Luxembourg
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
KIWA TBU DE (NB 0799) performed ITT under system 3 and issued test reports
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
-
9. Declared performance
Harmonised technical specification EN 13984:2013

| Essential characteristics | | | Performance | | |
|--|----------------|-------------------------|-------------|---------|---------|
| PROPERTY | METHOD | UNITS | NOMINAL | MINIMUM | MAXIMUM |
| Water vapour transmission (sd) | EN 1931 | m | 5 | 2 | 10 |
| Density of water vapour flow rate (g) | EN 1931 | kg / (m ² s) | 0,8E-7 | 0,4E-7 | 2,04E-7 |
| Durability (exposure to artificial ageing) | | | | | |
| Water vapour transmission properties | EN 1931 | pass / no pass | pass | - | - |
| Water tightness | EN 1928 (A) | pass / no pass | pass | - | - |
| Reaction to fire | EN ISO 11925-2 | class | E | - | - |
| Maximum tensile force (MD) | EN 12311-2 | N/50mm | 200 | 160 | - |
| Elongation at max. tensile force (MD) | EN 12311-2 | % | 38 | 25 | - |
| Maximum tensile force (XD) | EN 12311-2 | N/50mm | 170 | 110 | - |
| Elongation at max. tensile force (XD) | EN 12311-2 | % | 38 | 23 | - |
| Resistance to tearing MD (nail shank) | EN 12310-1 | N | 240 | 180 | - |
| Resistance to tearing XD (nail shank) | EN 12310-1 | N | 240 | 180 | - |
| Resistance to impact | EN 12691 | mm | (+) | | |
| Joint strength | EN 12317-2 | N/5cm | (+) | | |
| Durability (against alkali) | | | | | |
| Elongation at max. tensile force (MD) | EN 12311-1 | pass / no pass | (+) | | |
| Elongation at max. tensile force (XD) | EN 12311-1 | pass / no pass | (+) | | |

(+): No Performance Determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Arsène Schiltz

Managing and Works Director - DuPont Luxembourg

Luxembourg, 01/07/2013