

TYVEK® FLEXWRAP NF

Flexible high performance tape for air and water tight seals around sills, windows, doors and penetrations



Length: 23 m
Width: 15 cm



Applications:

- Window and door sills, pipe penetrations, chimney breasts, and other irregular penetrations
- Internal and external use

Benefits:

Superior protection /air and watertight seals

- Helps seal the building envelope
- Creates more airtight seals compared to standard tapes used on irregular shapes/penetrations

Easy installation

- Packaged in ready-to-use rolls
- No requirement for additional fixings
- Approx. 50% quicker to fit compared to standard tapes and seals

Superior durability

- Extendable tape constructed with a durable Tyvek® top-sheet, a premium butyl adhesive layer, and a specially designed release liner
- Allows for structural movements
- UV resistant

Excellent adhesion performance

- Ensures continuity, compatibility and integrity with all Tyvek® breather membranes, AirGuard® AVCLs and other membranes at penetrations
- 100% butyl adhesive performs over a wide temperature range
- Compatible with most common building materials



Installation around pipes



Installation around windows



Technical Data

Thickness	1.6 mm
Coverage	5.2 m ²
Colour	white (black adhesive)
Rolls per box	1
Temperature resistance	from - 30 °C till + 80 °C (temporary 100 °C)
Elongation	ca. 160 % (2.6 x of the original length)
Processing temperature	> 0 °C
UV resistance	4 months

INSTALLATION GUIDELINES

SURFACE PREPARATION

The surface must be free from dirt, moisture, ice, grease and other materials which could reduce the adhesion. Tyvek® FlexWrap NF is to be installed when dry and at temperatures above 0 °C.

INSTALLATION

- Properly position Tyvek® FlexWrap NF around the surface to seal.
- Minimise wrinkles and bubbles by smoothing the surface and by repositioning as necessary.
- Apply pressure by hand along the entire surface to achieve a good bond to the substrate. (After pressure has been applied repositioning will be difficult.)
- After completion of the installation Tyvek® FlexWrap NF has to be covered within 4 months with the appropriate building materials.

Installation around beams and joists



Watch the installation video for more details
goo.gl/dZGcqa



DuPont Protection Solutions
Bristol Business Park
Coldharbour Lane
Bristol
BS16 1QD
Tel 01275 33 76 60

www.construction.tyvek.co.uk



FOR
GREATER
GOOD™