

PERMABASE[®] TAPE TECHNICAL DATA SHEET

MANUFACTURER

Distributed by:

UNIFIX inc
 Subsidiary of National Gypsum Company
 35, rue Unifix
 Bromont, Qc J2L 1N5
 CANADA
 www.unifixinc.com

National Gypsum Company
 2001 Rexford Road
 Charlotte, NC 28211
 (704) 365-7300
 www.nationalgypsum.com

Technical Information
 USA: 1-800-NATIONAL
 Canada: 1-800-461-0955
 International: 1-450-534-0955

PermaBase[®] is a registered trademark of National Gypsum Company.

DESCRIPTION

PermaBase tape is an alkali resistant fiberglass tape especially designed to reinforce PermaBase cement board joints and corners.

ADVANTAGES

- Resistant to Alkalis
- Interior and exterior uses
- Choice of several widths and lengths
- Also available with pressure sensitive adhesive applied on one side.
- Easy to embed due to its large openings

INSTALLATION

Trowel bonding material to completely fill the tapered recessed board joints and gaps between each panel.

On non-tapered joints apply a 6" wide, approx. 1/16" thick coat of bonding material over entire joint.

For all joints, immediately embed the tape fully into applied bonding material and allow hardening.

If the tape has one side covered with pressure sensitive adhesive, it can be directly applied on the board's surface and then covered with the bonding material.

AVAILABLE SIZES

Rolls with self-adhesive
 2" x 50' (50 mm x 15,2 m)
 2" x 250' (50 mm x 76,2 m)
 3" x 150' (75 mm x 45,7 m)**
 4" x 150' (101 mm x 45,7m)*

Rolls without self-adhesive
 2" x 50' (50 mm x 15,2 m)*
 2" x 100' (50 mm x 30,5 m)*

* Available in USA only

** Available in Canada only

WARRANTY

Please contact us to get the information on warranty.

TECHNICAL DATA

Property	Imperial	Metric
Yarns	75 1/0 Fiberglass	680 Dtex Fiberglass
Pattern	8x7.5 yarns/inch	3,15 x 3 yarns / cm
Tensile	64 x 60 lb/inch (min)	570 x 534 N/5cm (min)
Weight	3.45 oz/sq.yd	117 g/m ²
Coating	PVC Plastisol	PVC Plastisol

Job Name: _____

Contractor: _____

Date: _____

Submittal Approvals: (Stamp or signature)

