

# isafe advanced safety flooring

cleaning and maintenance methods and guidance



Your isafe advanced safety floor, protected by Hyperguard+ PUR, is easy to clean and maintain by simply following the methods shown below.

## MANUAL



1. Sweep up dust & dirt, removing large debris



2. Apply alkaline cleaning fluid to the floor in the correct dilution (rate depends on cleaner used and level of soiling)



3. Scrub with a deck scrubber or cleaning pad



4. Rinse with water then remove dirty water with a mop and allow to dry - use a two compartment bucket to avoid mixing clean and dirty water

## MECHANICAL



1. Vacuum up dust and dirt, removing large debris



2. Apply alkaline cleaning fluid to the floor in the correct dilution (rate depends on cleaner used and level of soiling)



3. Mechanically scrub using a rotary cleaning machine fitted with a cleaning pad of the correct size



4. Wet vacuum residual wetness, rinse with clean water and vacuum dry

## CLEANING PRODUCTS: CLEANING FLUIDS & AGENTS

### Nova Safety Floor Cleaner by British Nova Works Ltd

T: 01295 254030 F: 01295 254061 E: sales@britishnova.co.uk

### CC Dr Schutz PU Cleaner by CC Dr Schutz

T: 01296 437827 F: 01296 334219 E: info@floorcare24.com

### Prochem A250 Alkleen, Prochem A217 Ultrapac Renovate & Prochem B195 Coffee Stain Remover All by Prochem

T: 020 8974 1515 F: 020 8974 1511 E: sales@prochem.co.uk



0800 032 3970  
[www.itecfloors.co.uk](http://www.itecfloors.co.uk)  
[info@itecfloors.co.uk](mailto:info@itecfloors.co.uk)

## CLEANING PRODUCTS: MACHINES & EQUIPMENT

### AVAILABLE FROM THE FOLLOWING SUPPLIERS:

#### CSA

T: 01954 251573 F: 01954 251931 E: csaeagle@fsbdial.co.uk

#### Prochem Europe Ltd

T: 020 8974 1515 F: 020 8974 1511 E: sales@prochem.co.uk

#### Rotowash (UK) Ltd

T: 020 8847 4545 F: 020 8569 7906 E: cleanfloors@rotowash.com

Medium duty cleaning pads should be used for isafe advanced safety flooring

## HINTS AND TIPS

1. Give consideration to tailoring a cleaning regime to the levels and types of traffic to which the area will be exposed to. Those areas subject to heavy trafficking will need to be cleaned more often than areas which are subject to less traffic.
2. Use cleaning fluids and agents as shown within this guide or **demonstrably equivalent** versions. Adhere to stated levels of dilution and the manufacturer's instructions. **Do not mix** cleaning fluids. Always check the suitability of cleaners for use on vinyl floors. **Do not use** fluids or agents containing pine oil.
3. Protect newly installed floors from other construction trades. Cover and protect newly laid isafe floor finishes during construction periods with a suitable non-staining protective covering.
4. Some materials are known to stain vinyl floors, including (but not limited to): asphalt, bitumen, wet cardboard, dyes from literature or packaging print, wet hardboard, rubber backed mats, furniture rests and wheels, some shoes without anti-staining soles, heat degradations, some chemicals used in cleaning products including pine oil, posters and powder paints and certain hair dyes.