

# Corotop® STRONG 160

The high-grammature membrane with strong structure. It does not break under heavy load or increased friction and thus it is recommended especially on fully-boarded roofs. Light colour reflects sun rays, what provides better insulation. Corotop Strong means the same quality for many years of usage and guaranteed durability.

## Application:

- the membrane dedicated on roofs with full or part-boarding
- initial underlay for thermally insulated, ventilated, sloping roofs
- to be used to most types of roof coverage, particularly under ceramic, concrete and metal tiles

## Advantages:

- minimizes heat loss
- regulates two-way vapour permeability
- protects thermal-insulation against damping
- the product extremely durable and resistant to damages
- also available in version with 2 adhesive stripes (Corotop Strong 160+)



GRAMMATURE  
160 g/m<sup>2</sup>



REACTION TO FIRE  
CLASS E



VAPOUR  
PERMEABILITY (SD)  
0,02 m



RESISTANCE  
TO WATER PENETRATION  
CLASS W1



RESISTANCE TO UV  
3 MONTHS



RESISTANCE TO TEARING  
(NAIL SHANK) ALONG/ACROSS:  
190 N / 275 N

Name	Size	Colour	Package
Corotop® STRONG 160	1,5m x 50r.m. = 75m <sup>2</sup>	beige-white	24 rolls
Corotop® STRONG 160+	1,5m x 50r.m. = 75m <sup>2</sup>	beige-white	24 rolls