



Never compromise on quality!



SEAL IT PRIMER

Primer For Use On Bitumen Roofs Prior To Use Of Seal It Liquid Membrane

Description:

A one part solvent-free primer for preparation of bitumen surfaces and roofing felt prior to the application of SEAL IT LIQUID MEMBRANE or EASISEAL PRO Weatherproofing Compound.

Benefits:

- Enhances the bond strength of SEAL IT LIQUID MEMBRANE and EASISEAL PRO to bitumen based, asphalt and felt substrates.
- Quick and easy to use.
- Blocks surface staining from bitumen coatings.

Preparation

Surfaces to be primed should be free from dirt, oil, grease, dust or loosely bound coatings or any other contaminants that may affect adhesion. Organic growth should be removed/treated with Bond It MOULD STOP. Surfaces MUST be dry prior to application.

Application

Temperature during application of primer **must be** above 5°C. Apply a single coat of SEAL IT PRIMER to the surface with a brush or roller. Follow coverage rate to ensure minimum thickness is achieved. Leave to fully cure, normally overnight, in cold weather it may require 48 hours to fully cure. White patches in the film indicate it requires more drying time.

It is essential that bituminous materials are completely covered with SEAL IT PRIMER prior to application of SEAL IT LIQUID MEMBRANE. Particular care must be given to rough surfaces such as bitumen felt, where any gaps in primer coverage can lead to product failure. Two coats of SEAL IT PRIMER are required on uneven surfaces and over waterbased bitumen coatings. Allow each coat to dry fully before overcoating.

Continue with the application of SEAL IT LIQUID MEMBRANE or EASISEAL PRO as per the Technical Datasheet/package details. It is recommended that SEAL IT REINFORCING MAT is bedded into the SEAL IT LIQUID MEMBRANE coating to extend the lifespan of the product over bitumen substrates.

We recommend a small discreet area

approximately 1m² is treated with the SEAL IT LIQUID MEMBRANE prior to applying to the full surface area for the purpose of identifying any adverse reaction between product and the substrate.

All colours of SEAL IT LIQUID MEMBRANE/ EASISEAL PRO can be used but discolouration may occur where primer coverage is incomplete or with waterbased bitumen coatings.

Cleaning Of Tools

Clean brushes or rollers with soap and water before the material has a chance to harden.

Container Size

2.5L.

Coverage

1 litre of SEAL IT OCRS PRIMER is sufficient for approximately 2-3m².

Colour

Clear.

Storage Conditions

Shelf life is 12 months when stored between 5°C and 30°C.

Disposal of Containers

Do not leave empty containers where residues could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Specification Summary

Cure Speed @ 18°C	18 hours
Application Temperature	5- 25°C
SG	ca.1.03 g/cm ³
Solids Content	Approx. 30%

Order Information:

Colour:	Clear
Code:	BDOCRSP2
Size:	2.5L
Barcode:	5060021372895



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V1 01/01/20
Supersedes: