### **DECLARATION OF PERFORMANCE**

According to ANNEX III of the regulation (EU) N° 305/2011



**No.** FB747-50 – 20160216

1. Unique identification code of the product-type: Nullifire FB747-50

Intended use/es: A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. Manufacturer: tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT

5. System/s of AVCP: System 1

**6b.** European Assessment Document: ETAG 026, edition 2011 used as European Assessment

Document

**European Technical Assessment:** Warrington Certification Limited issued European Technical Approval

- ETA14/0112

**Technical Assessment Body:** 

**Notified Body:** 

Warrington Certification Limited 1121, Warrington Certification Limited

#### 7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification	
Safety in Case of Fire			
Reaction to fire	Class F	EN13501-1	
Resistance to fire	Up to El120 and E120. Resistance to fire	BS EN1366-3:2009	
	performance & field of application in accordance with	EN 13501-2 as given in	
	BS EN 1366-3: 2009. Classified in accordance with	Annex C	
	EN 13501-2, as given in Annex C. See ETA14/0112		
	clause 3.2		
Hygiene, Health and Environment			
Air permeability	See clause 3.3 ETA 14/0112	BS EN 1314-1	
Dangerous substances	All dangerous chemical substances are below the		
	classification limits of 67/548/EEC. See ETA14/0112		
	clause 2.5		
Safety in Use			
Airborne sound insulation	See ETA 14/0112 clause 3.9 – Rw(C;C <sub>tr</sub> )= 24(-2;-3)		
Energy, Economy and Heat Retention			
Service & Durability	Z <sub>1</sub> .	ETAG 026-3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings At Wigan on 16th February 2016

## **DECLARATION OF PERFORMANCE**

According to ANNEX III of the regulation (EU) N° 305/2011



#### Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# CE

tremco illbruck Limited,

Coupland Road, Hindley Green, Wigan. WN2 4HT UK

14

1121-CPR-JA5031

FB747-50-20160216

www.nullifire.com/FB747-50/

EN 1366-3 2009

ETA 14-0112

ETAG 026, Parts 1 and 2

Coated mineral wool board to reinstate the fire resistance performance of rigid and flexible wall constructions where they are penetrated by various cables and metallic pipes.

Essential Characteristic	Performance		
Safety in Case of Fire			
Reaction to fire	Class F		
Resistance to fire	Up to EI120 and E120. Resistance to fire performance & field of application in accordance with BS EN 1366-3: 2009. Classified in accordance with EN 13501-2, as given in Annex C. See ETA14/0112 clause 3.2		
Hygiene, Health and Environment			
Dangerous Substances	All dangerous chemical substances are below the classification limits of 67/548/EEC. See ETA14/0112 clause 2.5		
Air permeability	See clause 3.3 ETA 14/0112		
Airborne sound insulation	See ETA 14/0112 clause 3.9 – Rw(C;C <sub>tr</sub> )= 24(-2;-3)		
Energy, Economy and Heat Retention			
Service & Durability	Z <sub>1</sub> .		
Other	Not applicable/No performance determined		