DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FR270 - 20160224

1. Unique identification code of the product-type: FR270

2. Intended use/es: Nullifire FR 270 FIRE STOP HIGH STRENGTH FAST CURING STRUCTURAL COMPOUND is a gypsum based mortar material, used to reinstate the fire performance of floor constructions where they have been provided with apertures for the penetration of multiple services.

3. Manufacturer: tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT

5. System/s of AVCP: System 1

6. European Assessment Document: ETAG 026 edition 2011 used as EAD European Technical Assessment: ETA 14/0098 of 09/04/2014 Warrington Certification Limited 1121, Warrington Certification Limited

7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification	
Safety in Case of Fire			
Reaction to fire	Class F	EN13501-1	
Resistance to fire	Up to EI 120 Resistance to fire performance & field of	EN13501-2	
	application in accordance with EN13501-2 See ETA	EN1366-3: 2009	
	14/0098 - Annex C		
Hygiene, Health and Environment			
Dangerous Substances	Does not contain dangerous substances	Declaration of	
	See ETA 14/0098 Clause 3.5	Manufacturer	
Energy, Economy and Heat Retention			
Service & Durability	Z ₁ intended for use in internal conditions with		
	humidity ≥ 85% RH, temperatures 0/+40 °C, without	ETAG 026-2	
	exposure to rain or UV in accordance with EOTA	ETAG 020-2	
	Technical Report TR024: 2009		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings At Wigan on 24 February 2016

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FR270 - 20160224

(€
tremco illbruck Limited,
Coupland Road, Hindley Green, Wigan. WN2 4HT UK
14
1121-CPR-JA5027
FR270 – 20160224
www.nullifire.com/FR270/
EN 1366-3: 2009
14/0098
ETAG 26, Part 1

Nullifire FR 270 FIRE STOP HIGH STRENGTH FAST CURING STRUCTURAL COMPOUND is a gypsum based mortar material, used to reinstate the fire performance of floor constructions where they have been provided with apertures for the penetration of multiple services.

ETAG 26, Part 2

Essential Characteristic	Performance		
Safety in Case of Fire			
Reaction to fire	Class F		
Resistance to fire	Up to El 120 Resistance to fire performance & field of application in accordance with EN13501-2 See ETA 14/0098 - Annex C		
Hygiene, Health and Environment			
Dangerous Substances	Does not contain dangerous substances See ETA 14/0098 Clause 3.5		
Energy, Economy and Heat Retention			
Service & Durability	Z₁ intended for use in internal conditions with humidity ≥ 85% RH, temperatures 0/+40 °C, without exposure to rain or UV in accordance with EOTA Technical Report TR024: 2009		
Other	NPD		