

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FS705 – 20160216

1. **Unique identification code of the product-type:** FS705

2. **Intended use/es:** An acrylic based graphite sealant used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. **Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT

5. **System/s of AVCP:** System 1

6b. **European Assessment Document:** ETAG 026, edition 2011  
used as European Assessment Document

**European Technical Assessment:** Warrington Certification Limited issued European Technical Approval – ETA 14/0111

**Technical Assessment Body:** Warrington Certification Limited  
**Notified Body:** 1121, Warrington Certification Limited

7. **Declared performance/s:**

Essential Characteristic	Performance	Harmonised Technical Specification
<b>Safety in Case of Fire</b>		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to EI240 and E180. Resistance to fire performance & field of application in accordance with EN1366-3: 2009. See ETA 14/0111 clause 3.2 - Annex C. Classified in accordance with EN 13501-2, as given in Annex C	EN1366-3: 2009 EN 13501-2, as given in Annex C
<b>Hygiene, Health and Environment</b>		
Air permeability	See clause 3.3 ETA 14/0111	BS EN 1314-1
Dangerous Substances	All dangerous chemical substances are below the classification limits of 67/548/EEC. See ETA 11/0111 Clause 3.5	
<b>Energy, Economy and Heat Retention</b>		
Service & Durability	Z <sub>1</sub> .	ETAG 026-3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**  
M. Liptrot, Business Unit Director Sealants & Coatings  
At Wigan on 16<sup>th</sup> February 2016



# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

## Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

<b>CE</b>	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 1121-CPR-JA5030 FS705 – 20160216 www.nullifire.com/FS705	
EN 1366-3: 2009 ETA 14-0111 ETAG 026, Parts 1 and 2 An acrylic based graphite sealant used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
<b>Safety in Case of Fire</b>	
Reaction to fire	Class F
Resistance to fire	Up to EI240 and E180. Resistance to fire performance & field of application in accordance with EN1366-3: 2009. See ETA 14/0111 clause 3.2 - Annex C. Classified in accordance with EN 13501-2, as given in Annex C
<b>Hygiene, Health and Environment</b>	
Air permeability	See clause 3.3 ETA 14/0111
Dangerous Substances	All dangerous chemical substances are below the classification limits of 67/548/EEC. See ETA 11/0111 Clause 3.5
<b>Energy, Economy and Heat Retention</b>	
Service & Durability	Z <sub>1</sub> .
Other	Not applicable/No performance determined