DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FS711 - 20160216

1. Unique identification code of the product-type: FS711

2. Intended use/es: Is an ablative coating applied to mineral wool board used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. Manufacturer: tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT, UK

System/s of AVCP: System 1

6. European Assessment Document: ETAG 026 edition 2011 part 2 used as European Assessment

Document (EAD)

European Technical Assessment: ETA 14/0113 of 25/04/2014
Technical Assessment Body: Warrington Certification Limited
Notified Body: 1121, Warrington Certification Limited

7. Declared performance/s:

For Penetration seals (ETAG 026 Part 2)

Essential Characteristic	Performance	Harmonised Technical Specification					
Safety in Case of Fire							
Reaction to fire	Class F	EN13501-1					
Resistance to fire	Up to El60. Resistance to fire performance & field of	EN13501-2					
	application in accordance with EN13501-2 See ETA						
	14/0113 clause 3.2 - Annex C						
Hygiene, Health and Environment							
Dangerous Substances	Does not contain dangerous substances						
Energy, Economy and Heat Retention							
Service & Durability	ice & Durability Z ₁ ETAG 026-3						

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

S	igned	for	and	on	behalf	of	the	manu	facture	r by:
---	-------	-----	-----	----	--------	----	-----	------	---------	-------

M. Liptrot, Business Unit Director Sealants & Coatings
At Wigan on 16 February 2016

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.



CE

tremco illbruck Limited,

Coupland Road, Hindley Green, Wigan. WN2 4HT UK

14

1121-CPR-JA5032

FS711 - 20160216

www.nullifire.com/FS711/

EN 1366-3: 2009

ETA 14-0113

ETAG 26, Part 3

Is an ablative coating applied to mineral wool board used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

Essential Characteristic	Performance					
Safety in Case of Fire						
Reaction to fire	Class F					
	Field of application to EN13501-2					
Resistance to fire	Up to El60, see ETA 14/0113 clause 3.2 -					
	Annex C					
Hygiene, Health and Environment						
Dangerous Substances	Does not contain dangerous substances					
Dangerous Substances	See ETA 14/0113 Clause 3.5					
Air Permeability	See ETA 14/0113 Clause 3.3					
Energy, Economy and Heat Retention						
Service & Durability	Z ₁					
Other	Not applicable/No performance determined					