

Revision Date 05/12/2013  
 Revision 7  
 Supersedes date 27/02/2013

# INSTARMAC

## SAFETY DATA SHEET ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc  
 Danny Morson Way  
 Birch Coppice Business Park  
 Dordon, Tamworth  
 Staffordshire. B78 1SE  
 United Kingdom  
 Tel: +44 (0) 1827 872244  
 Fax: +44 (0) 1827 874466  
 email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

+44 (0)7971 217 347

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; Skin Sens. 1 - H317; STOT SE 3 - H335
Environment	Aquatic Chronic 3 - H412

##### Classification (1999/45/EEC)

Xi; R37/38, R41. R43. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains PORTLAND CEMENT

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P501	Dispose of contents/container in accordance with local regulations.

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### Supplementary Precautionary Statements

P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P321	Specific treatment (see medical advice on this label).
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

BLACK PIGMENT	1-10%
<b>CAS-No.: 1133-86-4</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
CALCIUM CARBONATE POWDERS	30-60%
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
POLYVINYL ALCOHOL AND SILANE	< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
PORTLAND CEMENT	30-60%
<b>CAS-No.: 65997-15-1</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R37/38,R41. R43.

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

S-TRIAZINE DERIVATIVE <span style="float: right;">&lt; 1 %</span>	
<b>CAS-No.:</b> 886-50-0	<b>EC No.:</b> 212-950-5
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) N;R50/53.
VINYL ACETATE COPOLYMER <span style="float: right;">&lt; 1 %</span>	
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### **4.1. Description of first aid measures**

##### **General information**

Risk of serious damage to eyes.

##### **Inhalation**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

##### **Ingestion**

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

##### **Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

##### **Eye contact**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

#### **4.3. Indication of any immediate medical attention and special treatment needed**

### SECTION 5: FIREFIGHTING MEASURES

#### **5.1. Extinguishing media**

##### **Extinguishing media**

Water. Foam.

#### **5.2. Special hazards arising from the substance or mixture**

##### **Unusual Fire & Explosion Hazards**

No unusual fire or explosion hazards noted.

#### **5.3. Advice for firefighters**

##### **Special Fire Fighting Procedures**

No specific fire fighting procedure given.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet.

#### **6.2. Environmental precautions**

Do not allow to enter drains, sewers or watercourses.

#### **6.3. Methods and material for containment and cleaning up**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### 6.4. Reference to other sections

#### SECTION 7: HANDLING AND STORAGE

##### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

##### 7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

##### 7.3. Specific end use(s)

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BLACK PIGMENT	WEL		3.5 mg/m <sup>3</sup>			
CALCIUM CARBONATE POWDERS			10 mg/m <sup>3</sup>			
POLYVINYL ALCOHOL AND SILANE			4 mg/m <sup>3</sup>			
PORTLAND CEMENT	WEL		10 mg/m <sup>3</sup>			
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

##### 8.2. Exposure controls

###### Protective equipment



###### Process conditions

Provide eyewash station.

###### Engineering measures

Provide sufficient ventilation for operations causing dust formation.

###### Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

###### Hand protection

Use suitable protective gloves if risk of skin contact.

###### Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

###### Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

###### Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1. Information on basic physical and chemical properties

Appearance	Powder, dust
Relative density	1.6-2.0 @ 20°C

##### 9.2. Other information

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

#### 10.5. Incompatible materials

##### Materials To Avoid

Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

##### Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

##### Ingestion

May cause discomfort if swallowed.

##### Skin contact

Prolonged contact with wet cement/mixture may cause burns.

##### Eye contact

Risk of serious damage to eyes.

### SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: DISPOSAL CONSIDERATIONS

#### General information

Dispose of waste and residues in accordance with local authority requirements.

#### 13.1. Waste treatment methods

### SECTION 14: TRANSPORT INFORMATION

#### General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Uk Regulatory References**

Chemicals (Hazard Information & Packaging) Regulations.

#### **Environmental Listing**

Control of Pollution Act 1974.

#### **Approved Code Of Practice**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### **Guidance Notes**

Workplace Exposure Limits EH40.

#### **EU Legislation**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

#### **National Regulations**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

### 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

#### **General information**

If further information on training is required contact Instarmac Group plc

**Revision Date** 05/12/2013

**Revision** 7

**Supersedes date** 27/02/2013

#### **Risk Phrases In Full**

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R37/38 Irritating to respiratory system and skin.

R43 May cause sensitisation by skin contact.

NC Not classified.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### **Hazard Statements In Full**

H318 Causes serious eye damage.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

## ULTRA FINEJOINT WALL & FLOOR GROUT ANTHRACITE

### Disclaimer

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244

Revision Date 03/11/2015  
 Revision 12  
 Supersedes date 17/03/2015

# INSTARMAC

## SAFETY DATA SHEET ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc  
 Danny Morson Way  
 Birch Coppice Business Park  
 Dordon, Tamworth  
 Staffordshire. B78 1SE  
 United Kingdom  
 Tel: +44 (0) 1827 872244  
 Fax: +44 (0) 1827 874466  
 email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

+44 (0)7971 217 347

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Not classified.  
 Human health Skin Irrit. 2 - H315; Eye Dam. 1 - H318; STOT SE 3 - H335  
 Environment Not classified.

Classification (1999/45/EEC)

Xi; R37/38, R41.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.

Precautionary Statements

P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER or doctor/physician.  
 P501 Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.



## ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

P321	Specific treatment (see medical advice on this label).
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

CALCIUM CARBONATE POWDERS		1-10%
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Natural Calcium Carbonate		30-60%
CAS-No.: 1317-65-3	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
POLYVINYL ALCOHOL AND SILANE		< 1 %
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Quartz		< 1 %
CAS-No.: 14808-60-7	EC No.: 238-878-4	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
VINYL ACETATE COPOLYMER		< 1 %
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	

## ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

WHITE OPC	30-60%
CAS-No.:	EC No.:
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R41,R37/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General information

Risk of serious damage to eyes.

Inhalation

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Extinguishing media

Water. Foam.

#### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

#### 5.3. Advice for firefighters

Special Fire Fighting Procedures

No specific fire fighting procedure given.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

#### 6.4. Reference to other sections

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

#### 7.2. Conditions for safe storage, including any incompatibilities

## ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

Store in closed original container at temperatures between 5°C and 30°C. Avoid frost.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
CALCIUM CARBONATE POWDERS			10 mg/m <sup>3</sup>			
Natural Calcium Carbonate			4 mg/m <sup>3</sup>			
POLYVINYL ALCOHOL AND SILANE			4 mg/m <sup>3</sup>			
Quartz	WEL		0.3 mg/m <sup>3</sup>			
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			
WHITE OPC	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

Provide sufficient ventilation for operations causing dust formation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

Hand protection

Use suitable protective gloves if risk of skin contact.

Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated.

When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance                      Powder, dust  
Relative density                1.6-2.0 @ 20°C

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

## ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

### 10.5. Incompatible materials

Materials To Avoid

Strong acids. Strong alkalis.

### 10.6. Hazardous decomposition products

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Ingestion

May cause discomfort if swallowed.

Skin contact

Prolonged contact with wet cement/mixture may cause burns.

Eye contact

Risk of serious damage to eyes.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

General information

Dispose of waste and residues in accordance with local authority requirements.

### 13.1. Waste treatment methods

## SECTION 14: TRANSPORT INFORMATION

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

## ULTRA FINEJOINT WALL & FLOOR GROUT CREAM

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing

Control of Pollution Act 1974.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

National Regulations

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

### 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

General information

If further information on training is required contact Instarmac Group plc

Revision Date 03/11/2015

Revision 12

Supersedes date 17/03/2015

Risk Phrases In Full

R37/38 Irritating to respiratory system and skin.

NC Not classified.

R41 Risk of serious damage to eyes.

Hazard Statements In Full

H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

### Disclaimer

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244

Revision Date 05/12/2013  
Revision 6  
Supersedes date 05/03/2013

# INSTARMAC

## SAFETY DATA SHEET ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ULTRA FINEJOINT WALL & FLOOR GROUT GREY

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc  
Danny Morson Way  
Birch Coppice Business Park  
Dordon, Tamworth  
Staffordshire. B78 1SE  
United Kingdom  
Tel: +44 (0) 1827 872244  
Fax: +44 (0) 1827 874466  
email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

+44 (0)7971 217 347

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; Skin Sens. 1 - H317; STOT SE 3 - H335
Environment	Aquatic Chronic 3 - H412

##### Classification (1999/45/EEC)

Xi; R37/38, R41. R43. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains PORTLAND CEMENT

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P501	Dispose of contents/container in accordance with local regulations.

## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### Supplementary Precautionary Statements

P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P321	Specific treatment (see medical advice on this label).
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

CALCIUM CARBONATE POWDERS	30-60%
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
INORGANIC PIGMENT	< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
POLYVINYL ALCOHOL AND SILANE	< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
PORTLAND CEMENT	30-60%
<b>CAS-No.: 65997-15-1</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R37/38,R41. R43.

## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

S-TRIAZINE DERIVATIVE <span style="float: right;">&lt; 1 %</span>	
<b>CAS-No.:</b> 886-50-0	<b>EC No.:</b> 212-950-5
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) N;R50/53.
VINYL ACETATE COPOLYMER <span style="float: right;">&lt; 1 %</span>	
<b>CAS-No.:</b>	<b>EC No.:</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### **4.1. Description of first aid measures**

##### **General information**

Risk of serious damage to eyes.

##### **Inhalation**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

##### **Ingestion**

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

##### **Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

##### **Eye contact**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

#### **4.3. Indication of any immediate medical attention and special treatment needed**

### SECTION 5: FIREFIGHTING MEASURES

#### **5.1. Extinguishing media**

##### **Extinguishing media**

Water. Foam.

#### **5.2. Special hazards arising from the substance or mixture**

##### **Unusual Fire & Explosion Hazards**

No unusual fire or explosion hazards noted.

#### **5.3. Advice for firefighters**

##### **Special Fire Fighting Procedures**

No specific fire fighting procedure given.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet.

#### **6.2. Environmental precautions**

Do not allow to enter drains, sewers or watercourses.

#### **6.3. Methods and material for containment and cleaning up**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.



## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### 6.4. Reference to other sections

#### SECTION 7: HANDLING AND STORAGE

##### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

##### 7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 30°C. This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf life in correct for sealed bags is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

##### 7.3. Specific end use(s)

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1. Control parameters

Name	STD	TWA - 8 Hrs	STEL - 15 Min	Notes
CALCIUM CARBONATE POWDERS		10 mg/m <sup>3</sup>		
INORGANIC PIGMENT		10 mg/m <sup>3</sup>		
POLYVINYL ALCOHOL AND SILANE		4 mg/m <sup>3</sup>		
PORTLAND CEMENT	WEL	10 mg/m <sup>3</sup>		
VINYL ACETATE COPOLYMER	WEL	4 mg/m <sup>3</sup>		

WEL = Workplace Exposure Limit.

##### 8.2. Exposure controls

###### Protective equipment



###### Process conditions

Provide eyewash station.

###### Engineering measures

Provide sufficient ventilation for operations causing dust formation.

###### Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

###### Hand protection

Use suitable protective gloves if risk of skin contact.

###### Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

###### Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

###### Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1. Information on basic physical and chemical properties

Appearance	Powder, dust
Relative density	1.6-2.0 @ 20°C

##### 9.2. Other information

## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

#### 10.5. Incompatible materials

##### Materials To Avoid

Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

##### Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

##### Ingestion

May cause discomfort if swallowed.

##### Skin contact

Prolonged contact with wet cement/mixture may cause burns.

##### Eye contact

Risk of serious damage to eyes.

### SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: DISPOSAL CONSIDERATIONS

#### General information

Dispose of waste and residues in accordance with local authority requirements.

#### 13.1. Waste treatment methods

### SECTION 14: TRANSPORT INFORMATION

#### General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Uk Regulatory References**

Chemicals (Hazard Information & Packaging) Regulations.

#### **Environmental Listing**

Control of Pollution Act 1974.

#### **Approved Code Of Practice**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### **Guidance Notes**

Workplace Exposure Limits EH40.

#### **EU Legislation**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

#### **National Regulations**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

### 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

#### **General information**

If further information on training is required contact Instarmac Group plc

**Revision Date** 05/12/2013

**Revision** 6

**Supersedes date** 05/03/2013

#### **Risk Phrases In Full**

R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R37/38	Irritating to respiratory system and skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### **Hazard Statements In Full**

H318	Causes serious eye damage.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

## ULTRA FINEJOINT WALL & FLOOR GROUT GREY

### Disclaimer

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244

Revision Date 05/12/2013  
 Revision 7  
 Supersedes date 05/03/2013

# INSTARMAC

## SAFETY DATA SHEET ULTRA FINEJOINT WALL & FLOOR GROUT LESTONE

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ULTRA FINEJOINT WALL & FLOOR GROUT LESTONE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc  
 Danny Morson Way  
 Birch Coppice Business Park  
 Dordon, Tamworth  
 Staffordshire. B78 1SE  
 United Kingdom  
 Tel: +44 (0) 1827 872244  
 Fax: +44 (0) 1827 874466  
 email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

+44 (0)7971 217 347

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; STOT SE 3 - H335
Environment	Not classified.

##### Classification (1999/45/EEC)

Xi; R37/38, R41.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

##### Label In Accordance With (EC) No. 1272/2008



##### Signal Word

Danger

##### Hazard Statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

##### Precautionary Statements

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P501	Dispose of contents/container in accordance with local regulations.

##### Supplementary Precautionary Statements

P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.

**ULTRA FINEJOINT WALL & FLOOR GROUT LIMESTONE**

P302+352

IF ON SKIN: Wash with plenty of soap and water.

P304+340

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312

Call a POISON CENTER or doctor/physician if you feel unwell.

P332+313

If skin irritation occurs: Get medical advice/attention.

P362

Take off contaminated clothing and wash before reuse.

P321

Specific treatment (see medical advice on this label).

P403+233

Store in a well-ventilated place. Keep container tightly closed.

P405

Store locked up.

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

CALCIUM CARBONATE POWDERS		30-60%
<b>CAS-No.:</b>	<b>EC No.:</b>	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
INORGANIC PIGMENT		< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
POLYVINYL ALCOHOL AND SILANE		< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
SHADECRETE CARDINAL RED		< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
VINYL ACETATE COPOLYMER		< 1 %
<b>CAS-No.:</b>	<b>EC No.:</b>	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	

## ULTRA FINEJOINT WALL & FLOOR GROUT LIMESTONE

WHITE OPC	30-60%
CAS-No.:	EC No.:
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xi;R41,R37/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### **4.1. Description of first aid measures**

##### **General information**

Risk of serious damage to eyes.

##### **Inhalation**

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

##### **Ingestion**

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

##### **Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

##### **Eye contact**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

#### **4.3. Indication of any immediate medical attention and special treatment needed**

### SECTION 5: FIREFIGHTING MEASURES

#### **5.1. Extinguishing media**

##### **Extinguishing media**

Water. Foam.

#### **5.2. Special hazards arising from the substance or mixture**

##### **Unusual Fire & Explosion Hazards**

No unusual fire or explosion hazards noted.

#### **5.3. Advice for firefighters**

##### **Special Fire Fighting Procedures**

No specific fire fighting procedure given.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet.

#### **6.2. Environmental precautions**

Do not allow to enter drains, sewers or watercourses.

#### **6.3. Methods and material for containment and cleaning up**

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

#### **6.4. Reference to other sections**

### SECTION 7: HANDLING AND STORAGE

#### **7.1. Precautions for safe handling**

Avoid spilling, skin and eye contact.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Avoid frost. Store in closed original container at temperatures between 5°C and 30°C.

## ULTRA FINEJOINT WALL & FLOOR GROUT LIMESTONE

### 7.3. Specific end use(s)

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
CALCIUM CARBONATE POWDERS			10 mg/m <sup>3</sup>			
INORGANIC PIGMENT			10 mg/m <sup>3</sup>			
POLYVINYL ALCOHOL AND SILANE			4 mg/m <sup>3</sup>			
SHADECRETE CARDINAL RED			10.00 mg/m <sup>3</sup>		4.00 mg/m <sup>3</sup>	
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			
WHITE OPC	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

##### 8.2. Exposure controls

###### Protective equipment



###### Process conditions

Provide eyewash station.

###### Engineering measures

Provide sufficient ventilation for operations causing dust formation.

###### Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

###### Hand protection

Use suitable protective gloves if risk of skin contact.

###### Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

###### Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

###### Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1. Information on basic physical and chemical properties

Appearance	Powder, dust
Relative density	1.6-2.0 @ 20°C

##### 9.2. Other information

#### SECTION 10: STABILITY AND REACTIVITY

##### 10.1. Reactivity

##### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

##### 10.3. Possibility of hazardous reactions

##### 10.4. Conditions to avoid

##### 10.5. Incompatible materials



## ULTRA FINEJOINT WALL & FLOOR GROUT LIMESTONE

### Materials To Avoid

Strong acids. Strong alkalis.

### 10.6. Hazardous decomposition products

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

#### Ingestion

May cause discomfort if swallowed.

#### Skin contact

Prolonged contact with wet cement/mixture may cause burns.

#### Eye contact

Risk of serious damage to eyes.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### General information

Dispose of waste and residues in accordance with local authority requirements.

### 13.1. Waste treatment methods

## SECTION 14: TRANSPORT INFORMATION

### General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

### 14.6. Special precautions for user

## ULTRA FINEJOINT WALL & FLOOR GROUT LIMESTONE

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### SECTION 15: REGULATORY INFORMATION

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

###### **Uk Regulatory References**

Chemicals (Hazard Information & Packaging) Regulations.

###### **Environmental Listing**

Control of Pollution Act 1974.

###### **Approved Code Of Practice**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

###### **Guidance Notes**

Workplace Exposure Limits EH40.

###### **EU Legislation**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

###### **National Regulations**

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

##### 15.2. Chemical Safety Assessment

#### SECTION 16: OTHER INFORMATION

###### **General information**

If further information on training is required contact Instarmac Group plc

**Revision Date** 05/12/2013

**Revision** 7

**Supersedes date** 05/03/2013

###### **Risk Phrases In Full**

R37/38 Irritating to respiratory system and skin.

NC Not classified.

R41 Risk of serious damage to eyes.

###### **Hazard Statements In Full**

H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

#### Disclaimer

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244

Revision Date 03/11/2015  
 Revision 12  
 Supersedes date 17/03/2015

# INSTARMAC

## SAFETY DATA SHEET ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc  
 Danny Morson Way  
 Birch Coppice Business Park  
 Dordon, Tamworth  
 Staffordshire. B78 1SE  
 United Kingdom  
 Tel: +44 (0) 1827 872244  
 Fax: +44 (0) 1827 874466  
 email@instarmac.co.uk www.instarmac.co.uk

#### 1.4. Emergency telephone number

+44 (0)7971 217 347

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; STOT SE 3 - H335
Environment	Not classified.

Classification (1999/45/EEC)

Xi; R37/38, R41.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Precautionary Statements

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P501	Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.

## ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

P321	Specific treatment (see medical advice on this label).
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Natural Calcium Carbonate		30-60%
CAS-No.: 1317-65-3	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
POLYVINYL ALCOHOL AND SILANE		< 1 %
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Quartz		< 1 %
CAS-No.: 14808-60-7	EC No.: 238-878-4	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
VINYL ACETATE COPOLYMER		< 1 %
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
WHITE OPC		30-60%
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R41,R37/38.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

## ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

### 4.1. Description of first aid measures

#### General information

Risk of serious damage to eyes.

#### Inhalation

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

#### Ingestion

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml).

#### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

#### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Water. Foam.

### 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

No specific fire fighting procedure given.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.

### 6.4. Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 30°C. Avoid frost.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

## ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
Natural Calcium Carbonate			4 mg/m <sup>3</sup>			
POLYVINYL ALCOHOL AND SILANE			4 mg/m <sup>3</sup>			
Quartz	WEL		0.3 mg/m <sup>3</sup>			
VINYL ACETATE COPOLYMER	WEL		4 mg/m <sup>3</sup>			
WHITE OPC	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

Provide sufficient ventilation for operations causing dust formation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

Hand protection

Use suitable protective gloves if risk of skin contact.

Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated.

When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance                      Powder, dust  
Relative density                1.6-2.0 @ 20°C

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

Materials To Avoid

Strong acids. Strong alkalis.

### 10.6. Hazardous decomposition products

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

## ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

### Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

### Ingestion

May cause discomfort if swallowed.

### Skin contact

Prolonged contact with wet cement/mixture may cause burns.

### Eye contact

Risk of serious damage to eyes.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### General information

Dispose of waste and residues in accordance with local authority requirements.

#### 13.1. Waste treatment methods

## SECTION 14: TRANSPORT INFORMATION

### General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

#### 14.4. Packing group

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Uk Regulatory References

Chemicals (Hazard Information & Packaging) Regulations.

## ULTRA FINEJOINT WALL & FLOOR GROUT WHITE

Environmental Listing

Control of Pollution Act 1974.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

National Regulations

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

15.2. Chemical Safety Assessment

### SECTION 16: OTHER INFORMATION

General information

If further information on training is required contact Instarmac Group plc

Revision Date 03/11/2015

Revision 12

Supersedes date 17/03/2015

Risk Phrases In Full

R37/38 Irritating to respiratory system and skin.

NC Not classified.

R41 Risk of serious damage to eyes.

Hazard Statements In Full

H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

#### Disclaimer

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244