

**ULTRA
TILE**

FLEXJOINT

Ultimate Flexi Grout

Features

- Kitchens, Bathrooms, Swimming Pools, Power Showers etc.
- Underfloor Heating
- Super Fine Texture
- Mould & Stain Resistant
- Water Repellent
- Wipes Clean Easily
- Polymer Modified
- Colours: White, Cream, Jasmine, Beige, Limestone, Chocolate, Titanium, Grey, Charcoal and Anthracite

UltraTile FlexJoint grout has been specifically designed for areas when movement or vibration is likely. With excellent joint filling capacity, the product allows for joints up to 20mm to be filled in one application.

**MATCHING
SILICONES**



- + 1 mm**
+ 20 mm
JOINT THICKNESS
- WATER REPELLENT TECHNOLOGY**
- INTERNAL & EXTERNAL**
- 30-60 MINS**
TYPICAL POT LIFE
- CG2**
MANUFACTURED TO MEET EN13888 CLASSIFICATION

**ULTRA
TILE**

FLEXJOINT

Ultimate Flexi Grout

UltraTile FlexJoint grout has been specially designed for areas where movement or vibration is likely. With excellent joint filling capacity, the product allows for joints up to 20mm to be filled in one application. Polymer has been added to the formulation to increase flexibility and to provide a virtually impermeable set. UltraTile FlexJoint grout is suitable for use with most common tile applications including natural stone, porcelain, conglomerate and ceramic wall and floor tiles.

INSTRUCTION DATA

PRECAUTION

Certain tiles may suffer from discoloration or scratching when using grouts. We would recommend that a test application be carried out prior to grouting. Our grouts go through stringent checks to ensure quality and colour, however due to the use of raw materials we suggest a trial area to ensure colour is consistent and as expected.

SURFACE PREPARATION

Ensure that the adhesive is completely set and that the tiles are firmly fixed. Ensure that joints are free from excess adhesive, dust, grease or any other contaminants.

MIXING

UltraTile FlexJoint grout powder should be added slowly to clean water in a suitable container in the appropriate proportion of 2.75 parts powder to 1 part water for White and Cream. 3.25 parts powder to 1 part water for Jasmine, Beige and Titanium. 3.5 parts powder to 1 part water for Limestone, Chocolate, Grey, Charcoal and Anthracite. Mix until a smooth consistency is achieved, leave to stand for 2 minutes then remix. Do not mix more than can be used in a 30-60 minute period, do not re-wet or add too much water. This will cause a weakening of the grout and a tendency to crumble. In certain cases this may also lead to discoloration in the form of efflorescence.

APPLICATION

UltraTile FlexJoint grout should be applied to the surface using a rubber backed trowel or squeegee. Work the mixed material thoroughly into the joints, a small area at a time. Ensure that the joints are completely filled without voids before continuing. Excess grout should be removed as grouting proceeds. Any residue left on the face of the tile can be removed by wiping with a damp sponge when the grout has started

to firm (approximately 15 mins - when using a normal ceramic tile. On non-absorbent tiles such as porcelain, this may take up to an hour). Any dry film remaining once the job is complete can be polished off the face of the tiles with a soft dry cloth. Finishing when the grout is not firm to the touch, may lead to joints being emptied or potential colour variations.

TECHNICAL DATA

Packaging: 3kg and 10kg bags

Standard Conformities: CG2, EN13888

Initial Drying time: 10-15 min
(dependent on temperature)

Pot Life: 30-60 min*

Set Time: Within 24 hours*

Application Thickness: 1-20mm

Protein Free: Yes

Storage: This product must be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts.

Shelf Life: Unopened bags: 12 months in cool, dry conditions above 5°C and below 30°C.

*The above technical data is dependent on colour and temperature.

QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified/registered as being in conformity with BS EN ISO 9001, ISO 14001 and OHSAS 18001. UltraTile products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All UltraTile products are sold subject to our conditions of sale, copies of which may be obtained upon request.

HEALTH & SAFETY

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full Material Safety Data Sheet relating to this product is available from www.instarmac.co.uk.

Manufactured by **Instarmac Group plc**

Danny Morson Way, Birch Coppice Business Park, Dordon, Tamworth, Staffordshire B78 1SE

Tel: +44 (0)1827 872244 Fax: +44 (0)1827 874466. Enquiries: email@instarmac.co.uk Visit: www.instarmac.co.uk

Version9.04.2016

An **INSTARMAC**® Brand