

## Specification

Linoleum homogeneous floorcovering made by one single layer calandered on jute backing. Composition: linseed oil, wood and cork flour, natural resins, pigments. Product standard: EN ISO 24011.

**GARANTEE**  
**10 YEARS**

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto xf <sup>2</sup> 2 mm	Veneto xf <sup>2</sup> - Veneto xf <sup>2</sup> B <sub>1</sub> - Style Emme xf <sup>2</sup> - Style Elle xf <sup>2</sup> Veneto Essenza 2.5 mm	Veneto xf <sup>2</sup> 3.2 mm	Veneto Sicuro xf <sup>2</sup> 2.5 mm	Silencio xf <sup>2</sup> 3.8 mm	Veneto Acoustic Cork xf <sup>2</sup> 4.0 mm	Veneto Acoustic Cork xf <sup>2</sup> Veneto Acoustic Cork Essenza Style Emme Acoustic Cork xf <sup>2</sup> 4.4 mm	Etrusco xf <sup>2</sup> 2.5 mm	Linoleum Conductive xf <sup>2</sup> 2.5 mm	Linoleum SD Static Dissipative xf <sup>2</sup> 2.5 mm
Type of floorcovering	EN 686 EN 687	-	-	-	Linoleum on a foam backing	-	-	Linoleum on a corkment backing Linoleum on a corkment backing	-	-	-
CE Certification	EN 14041	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Classification	EN ISO 10874 Domestic Commercial Light industrial	Classes: 23 32 41	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 33 41	Classes: 23 33 41	Classes: 23 34 42	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43
<b>TECHNICAL CHARACTERISTICS</b>											
Surface Treatment		xf <sup>2</sup>	xf <sup>2</sup> (acrylic Essenza)	xf <sup>2</sup>	xf <sup>2</sup>	xf <sup>2</sup>	xf <sup>2</sup>	xf <sup>2</sup> (acrylic Essenza)	xf <sup>2</sup>	xf <sup>2</sup>	xf <sup>2</sup>
Total thickness	EN ISO 24346	2.0 mm	2.5 mm	3.2 mm	2.5 mm	3.8 mm	4.0 mm	4.4 mm	2.5 mm	2.5 mm	2.5 mm
Total weight	EN ISO 23997	ca. 2 400 g/m <sup>2</sup>	ca. 3 000 g/m <sup>2</sup>	ca. 3 900 g/m <sup>2</sup>	ca. 3 000 g/m <sup>2</sup>	ca. 3 450 g/m <sup>2</sup>	ca. 4 100 g/m <sup>2</sup>	ca. 4 600 g/m <sup>2</sup>	ca. 3 000 g/m <sup>2</sup>	ca. 3 000 g/m <sup>2</sup>	ca. 3 000 g/m <sup>2</sup>
Residual indentation	EN ISO 24343-1	ca. 0.07 mm	ca. 0.08 mm	ca. 0.10 mm	ca. 0.08 mm	≤ 0.20 mm	≤ 0.25 mm	≤ 0.25 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm
Flexibility	EN ISO 24344 Method A	≤ 25 mm Ø	≤ 30 mm Ø	≤ 40 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø
Form of delivery	EN ISO 24341	≤ 30 x 2 m	≤ 30 x 2 m	≤ 30 x 2 m	≤ 30 x 2 m	≤ 27 x 2 m or ≤ 27 x 1.95 m (subject to availability-please check upon order)		≤ 30 x 2 m	≤ 30 x 2 m	≤ 30 x 2 m	≤ 30 x 2 m
<b>TECHNICAL PERFORMANCES</b>											
Fire classification	EN 13501-1	Cr s1	Cr s1 (B <sub>1</sub> s1 for Veneto xf <sup>2</sup> B <sub>1</sub> )	Cr s1	Cr s1	Cr s1	Cr s1	Cr s1	Cr s1	Cr s1	Cr s1
Impact sound reduction	EN ISO 140-8 EN ISO 717-2	5 dB	6 dB	8 dB	6 dB	18 dB	15 dB	15 dB	6 dB	6 dB	6 dB
Impact sound in the room	NF S31-074	Class C < 85 dB	Class C < 85 dB	Class B < 75 dB	Class C < 85 dB	Class A < 65 dB	Class B < 75 dB	Class B < 75 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB
Impact sound reduction with Elafono*	EN ISO 140-8 EN ISO 717-2	14 dB	14 dB	15 dB	14 dB	Not applicable	Not applicable	Not applicable	14 dB	Not applicable	Not applicable
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)									
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Electrical resistance	EN 1081 ESD-approval SP method 2472 EN/IEC 61340-4-1	-	-	-	-	-	-	-	-	R <sub>1</sub> ≤ 10 <sup>8</sup> Ω R <sub>2</sub> ≤ 10 <sup>8</sup> Ω R ≤ 10 <sup>9</sup> Ω R ≤ 10 <sup>9</sup> Ω	R <sub>1</sub> ≤ 10 <sup>8</sup> Ω R <sub>2</sub> ≤ 10 <sup>8</sup> Ω 1x10 <sup>4</sup> < R < 1x10 <sup>9</sup> Ω R ≤ 10 <sup>9</sup> Ω
Slip resistance	EN 13893 DIN 51130	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R10	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9
Chemical resistance	EN ISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis									
Thermal resistance Underfloor heating	EN ISO 10456	0.012 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.019 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.040 m <sup>2</sup> K/W Suitable	0.042 m <sup>2</sup> K/W Suitable	0.045 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable
Light fastness	EN ISO 105-B02 Method 3	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Determination of antibacterial activity	EN ISO 22196	Naturally bactericidal									
Colours		20	72 (Veneto) - 10 (Veneto xf <sup>2</sup> B <sub>1</sub> ) 30 (Essenza) - 15 (Style Emme) 11 (Style Elle)	20	29	72 (Veneto) 15 (Style Emme) 11 (Style Elle) 14 (Etrusco)	20 on request	on request: 72 (Veneto) 30 (Essenza) 15 (Style Emme)	14	1	4

The above information is subject to modification for the benefit of further improvement. (11/15).

CUSTOMS TARIFF : 48205000000F

**DISCLAIMER:** Although the utmost care is taken, the data here given could differ and be subject to modifications from a technical point of view.

In its strive to improve its floor solutions, Tarkett reserves the right to modify its technical specifications, colours and materials at any moment and without prior notice. Please, check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (colour) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to service correctly and safely. Refer to Tarkett technical installation and maintenance directions, available at [www.tarkett.com](http://www.tarkett.com) or at your Tarkett dealer.

\*Elafono : 2,0mm traditional, 100% natural corkment underlay to be installed in combination with any compact Tarkett linoleum to get additional sound reduction (up to 15dB, depending on the product). Available in rolls ≤30 x 2m.

**Veneto xf<sup>2</sup> 2 mm**  
0200-0010-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Veneto xf<sup>2</sup> 2.5 mm**  
0200-0001-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Veneto xf<sup>2</sup> B<sub>1</sub> 2.5 mm**  
0200-0014-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Veneto xf<sup>2</sup> 3.2 mm**  
0200-0012-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Style Emme xf<sup>2</sup> 2.5 mm**  
0200-0034-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Style Elle xf<sup>2</sup> 2.5 mm**  
0200-0031-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Veneto Essenza 2.5 mm**  
0200-0011-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Veneto Sicuro xf<sup>2</sup>**  
0200-0005-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Silencio xf<sup>2</sup> 3.8 mm**  
0200-0027-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Etrusco xf<sup>2</sup> 2.5 mm**  
0200-0020-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Linoleum xf<sup>2</sup> SD 2.5 mm**  
0200-0017-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

**Linoleum Conductive xf<sup>2</sup> 2.5 mm**  
0200-0043-DoP-2013-07  
<http://professionals.tarkett.com>  
Manufactured by: Tarkett SpA  
05036 Normi - ITALY  
EN 14041:2004

Acoustic

Compact

<b>Veneto</b>	94% 76% Natural Renewable	100% 36% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Etrusco</b>	93% 77% Natural Renewable	100% 34% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Style</b>	96% 74% Natural Renewable	100% 30% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Elafono</b>	100% 85% Natural Renewable	100% 34% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS
<b>SD</b>	98% 58% Natural Renewable	100% 18% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Conductive</b>	96% 58% Natural Renewable	100% 18% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Silencio</b>	83% 65% Natural Renewable	100% 40% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS	<b>Acoustic Cork</b>	93% 77% Natural Renewable	100% 33% Recyclable	PHthalate FREE	Better Indoor Air Quality <100µg/m <sup>3</sup> *TVOC AT 28 DAYS