

### Description

ME316 is a special PP fleece with waterproof solid adhesive.

### Colour

Black

### Packaging

Item No.	Roll Length	Roll Width	Rolls/Box
398861	25 m	60 mm	10

### Technical Information

#### Application

- Surfaces must be dry and free of oil, grease, dust and other anti-adhesive components. Bonding to frozen surfaces is not possible. The substrate must offer sufficient load-bearing capacity. On porous or damp substrates or at low temperatures the use of primer ME904 is recommended.
- Detach the release paper and affix the tape on the centre of the overlap.
- Gradually peel off the release paper and adhere the tape whilst keeping it tension- and wrinkle-free to the substrate.
- To consolidate the bond apply firm pressure manually. Use of a seam roller will further improve the adhesion in most applications.

#### Health & Safety Precautions

Safety data sheet must be read and understood before use.



## ME316

### Endurance Tape

#### Usage / Purpose

Single-sided adhesive tape for interior and exterior use providing a high performing air and weather-tightness seal. Suitable for a wide variety of applications, including sealing of sheathing boards and for the durable bonding of illbruck commercial vapour barrier, and breather membranes. Particularly suited for sealing of joints between timber panels to maintain long-term performance. A permanent bond is achieved on all illbruck building protection membranes and PE, PA, PP, aluminium foils, concrete, brick and block, aerated concrete and wood used to create an airtight seal.

#### Key Benefits

- Interior and exterior use
- 6 month UV stability and outdoor exposure
- Can be used in partially open facades – low visibility branding when installed
- Quick and easy application
- Soft fleece backing
- Excellent permanent adhesive bond strength to most common substrates
- Compatible with all illbruck building protection membranes

**ME316**

## Endurance Tape



### Technical Service

tremco illbruck has a team of experienced Technical Service Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Service on 01942 251400.

### Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has

been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.;No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.;tremco illbruck Ltd. reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



### tremco illbruck Limited

Coupland Road, Hindley Green  
WN2 4HT Wigan  
United Kingdom  
T: +44 1942 251400  
F: +44 1942 251410

[info.uk@tremco-illbruck.com](mailto:info.uk@tremco-illbruck.com)  
[www.tremco-illbruck.co.uk](http://www.tremco-illbruck.co.uk)