

DECLARATION OF PERFORMANCE

in accordance with Annex 111 of Regulation (EU) No. 305/2011

(Construction Products Regulation)

1. Unique identification code of the product type:

ULTRA PROFLEX SP GREY

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

Product formulation reference X2006

3. Intended use as foreseen by the manufacturer of the construction product in accordance with harmonised technical specification:

Improved fast setting deformable cementitious adhesive with reduced slip

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

**Instarmac Group plc
Birch Coppice Industrial Estate
Danny Morson Way, Dordon
Tamworth B78 1SE
United Kingdom**

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 (2):

Not relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

System 3 + 4

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

The notified body Ceram, No. 1289 has carried out initial type testing to System 3 and issued Test report No. (124246)-17187

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued.

Not relevant

9. Declared performance

<u>Essential characteristics</u>	<u>Performance</u>	<u>Harmonised technical specification</u>
Bond Strength as:		
Early tensile adhesion	0.7 N/mm²	
Initial tensile adhesion	1.9 N/mm²	
 Durability for tensile		
Adhesion:		
After heat ageing	1.9 N/mm²	BSEN 12004:2007+A1:2012
After water immersion	1.4 N/mm²	
After freeze/thaw cycles	1.3 N/mm²	
 Reaction to Fire	Class E WFT	
 Release of dangerous		
Substances	See MSDS	

CLASSIFICATION - C2FTS1

10. The performance of the product identified in items 1 and 2 in conformity with the declared performance set out in item 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for on behalf of the manufacturer by:



..... (Signature)

Chris Murphy - Technical Director

Tamworth – 13.06.13

..... (Place & Date Issued)

DECLARATION OF PERFORMANCE

in accordance with Annex 111 of Regulation (EU) No. 305/2011

(Construction Products Regulation)

1. Unique identification code of the product type:

ULTRA PROFLEX SP WHITE

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

Product formulation reference X2007

3. Intended use as foreseen by the manufacturer of the construction product in accordance with harmonised technical specification:

Improved fast setting deformable cementitious adhesive with reduced slip

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

**Instarmac Group plc
Birch Coppice Industrial Estate
Danny Morson Way, Dordon
Tamworth B78 1SE
United Kingdom**

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 (2):

Not relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

System 3 + 4

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

The notified body Ceram, No. 1289 has carried out initial type testing to System 3 and issued Test report No. (124246) - 19871

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued.

Not relevant

9. Declared performance

<u>Essential characteristics</u>	<u>Performance</u>	<u>Harmonised technical specification</u>
Bond Strength as:		
Early tensile adhesion	0.7 N/mm ²	
Initial tensile adhesion	3.1 N/mm ²	
Durability for tensile Adhesion:		
After heat ageing	2.4 N/mm ²	
After water immersion	1.5 N/mm ²	BSEN 12004:2007+A1:2012
After freeze/thaw cycles	1.5 N/mm ²	
Reaction to Fire	Class E WFT	
Release of dangerous Substances	See MSDS	

CLASSIFICATION - C2FTS1

10. The performance of the product identified in items 1 and 2 in conformity with the declared performance set out in item 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for on behalf of the manufacturer by:



..... (Signature)

Chris Murphy - Technical Director

Tamworth – 13.06.13

..... (Place & Date Issued)