

DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

TREMCO
Lasting Performance

No. SX100 – 20140702

1. **Unique identification code of the product-type:** SX100
2. **Intended use/es:** Cement screed material for use internally in buildings – EN 13813:2002
3. **Manufacturer:** tremco illbruck Coatings Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
5. **System/s of AVCP:** System 4 (for internal uses)
- 6a. **Harmonised standard:** EN 13813:2002 (CA-C30-F10)

Notified body/ies: Not relevant

7. Declared performance/s:

EN 13813:2002 (Cement screed material for use internally in buildings (non-wearing surfaces))

| Essential Characteristic | Performance | Harmonised Technical Specification |
|---------------------------------|-------------|------------------------------------|
| Release of corrosive substances | CA | EN 13813:2002 |
| Compressive strength | C30 | EN 13813:2002 |
| Flexural strength | F10 | EN 13813:2002 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings
At Wigan on 7 April 2015



Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

TREMCO

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| CE | |
| tremco illbruck Coatings Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 SX100 – 20140702 tremco-europe.com/SX100/ | |
| EN 13813:2002 Cement screed material for use internally in buildings (non-wearing surfaces) | |
| Essential Characteristic | Performance |
| Release of corrosive substances | CA |
| Compressive strength | C30 |
| Flexural strength | F10 |