


TECHNICAL DATA	STANDARDS	Veneto xf ² ™ 2mm	Veneto xf ² ™ Veneto xf ² ™ B _n 2.5mm	Veneto xf ² ™ 3.2mm	Veneto Silencio xf ² ™ 3.8mm	Veneto Acoustic Cork xf ² ™ 4mm	Veneto Acoustic Cork xf ² ™ 4.4mm
Classification							
Classification	ISO 10874 (EN 685) domestic commercial light industrial	Classes: 23 32 41	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 33 41	Classes: 22 33 41	Classes: 23 34 42
Characteristics							
Surface Treatment		xf ² ™	xf ² ™	xf ² ™	xf ² ™	xf ² ™	acrylic
Total thickness	ISO 24346 (EN 428)	2.00mm	2.50mm	3.20mm	3.80mm	4.0mm	4.4mm
Total weight	ISO 23997 (EN 430)	ca. 2 400g/m ²	ca. 3 000g/m ²	ca. 3 900g/m ²	ca. 3 450g/m ²	ca. 4 100g/m ²	ca. 4 600g/m ²
Technical performances							
Reaction to fire	EN 13501-1	C _n s1	C _n s1 (B _n s1 for Veneto xf ² ™ B _n)	C _n s1	C _n s1	C _n s1	C _n s1
Residual indentation	ISO 24343 (EN 433)	ca. 0.07mm	ca. 0.08mm	ca. 0.10mm	≤ 0.20mm	≤ 0.25mm	≤ 0.25mm
Slip resistance	DIN 51130 EN 13893	R9 DS: ≥ 0.30	R9 DS: ≥ 0.30	R9 DS: ≥ 0.30	R9 DS: ≥ 0.30	R9 DS: ≥ 0.30	R9 DS: ≥ 0.30
Flexibility	ISO 23344 (EN 435 Method A)	≤ 25mm	≤ 30mm	≤ 40mm	≤ 30mm	≤ 30mm	≤ 30mm
Castor chair	ISO 4918 (EN 425)	Suitable for office chairs with castors type W (Norm EN 12529)					
Static electrical propensity	EN 1815	< 2kV	< 2kV	< 2kV	< 2kV	< 2kV	< 2kV
Chemical resistance	ISO 26987 (EN 423)	Resistant to dilute acids, oils, fats, current solvents and alkalis					
Thermal resistance Underfloor heating	ISO 10456 (EN 12524)	0.012m ² K/W Suitable	0.015m ² K/W Suitable	0.019m ² K/W Suitable	0.040m ² K/W Suitable	0.042m ² K/W Suitable	0.045m ² K/W Suitable
Light fastness	EN ISO 105-B02 Method 3	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Impact sound reduction	ISO 140-8 EN ISO 717-2	≤ 4dB	≤ 6dB	≤ 6dB	18dB	15dB	15dB
Impact sound reduction with Elafono*	ISO 140-8 EN ISO 717-2	14dB	14dB	14dB	Not applicable		
Acoustic improvement	NF S31-074	—	—	—	Class A (L _{n,e,w} < 65dB)	Class B (L _{n,e,w} < 75dB)	
Determination of antibacterial activity	ISO 22196	Yes, naturally					


*Elafono: 2.0mm traditional, natural corkment underlay to be installed in combination with any compact Tarkett linoleum to get additional sound reduction (up to -14dB, depending on the product). Available in rolls ≤ 30 x 2m.

The above information is subject to modifications for the benefit of further improvement (07/2015).

For more detailed technical information, please contact Tarkett.



Terracotta




Pumpkin

- 2.0mm: 14871 641
- 2.5mm: 14872 641
- 3.2mm: 14873 641
- 3.8mm: 14892 641
- 4.0mm: 14880 641
- 4.4mm: 14881 641

- 2.5mm: 14872 633
- 3.8mm: 14892 633
- 4.4mm: 14881 633

General Information



Laying direction:



Available in rolls
Rolls length: ≤30lm



Silencio
(3.8mm) Rolls length: ≤27lm



Acoustic
Cork
(4.0mm) Rolls length: ≤27lm



Acoustic
Cork
(4.4mm) Rolls length: ≤27lm

VENETO xf²™ Classical marbled Reds

Main Product Features

- Superior xf²™ protection for extreme mechanical and chemical toughness
- The classical marbled linoleum solution with soft or intense pattern variations for a timeless effect
- All 72 colours also available in Silencio xf²™ 18dB and on request on Acoustic Cork version

Surface Treatment



Sustainability Tag

Veneto xf²™

94% 76%	100% 36%	<100µg/m ³ Better Indoor Air Quality
Natural Renewable	Recyclable Recycled content	*TVOC AT 28 DAYS

Veneto Silencio xf²™

83% 65%	100% 40%	<100µg/m ³ Better Indoor Air Quality
Natural Renewable	Recyclable Recycled content	*TVOC AT 28 DAYS

Veneto Acoustic Cork xf²™

93% 77%	100% 33%	<100µg/m ³ Better Indoor Air Quality
Natural Renewable	Recyclable Recycled content	*TVOC AT 28 DAYS

Logistics Information



Available in rolls
Rolls length: ≤30lm



Silencio
(3.8mm) Rolls length: ≤27lm



Acoustic
Cork
(4.0mm) Rolls length: ≤27lm



Acoustic
Cork
(4.4mm) Rolls length: ≤27lm