



Never compromise on quality!

Published: May 2011

# SPRAY ADHESIVE

## High Strength Aerosol Adhesive

### Description

*A fast acting, easy to use adhesive in an aerosol can.*

### Uses

Bond It **SPRAY ADHESIVE** is a non-chlorinated, exceptionally powerful, long-lasting, multi purpose adhesive. It does not contain damaging or harmful materials such as CFC's or Methylene Chloride (Dichloromethane). For use on materials such as fabrics, wood, concrete, metal, plastic, rubber, paper, card and is particularly suited to bonding foam to foam. It is fitted with a variable discharge nozzle that controls the width of the spray fan; the more pressure applied to the nozzle the wider the fan. It is ideal for the fixing of carpets, carpet tiles, cork tile, underfelts and minor floor installations, for use in the furniture and automotive industries, especially for bonding foam to a variety of surfaces. Also suitable for use in repair and non-structural applications where a high strength bond is required. Note: This product should not be used for construction purposes such as unsupported head linings in vehicles and boats. It is NOT suitable for use with non rigid / plasticised PVC and should not be used on surfaces where temperatures may exceed 50°C.

### Application

SHAKE WELL BEFORE USE. ONLY USE IN WELL VENTILATED AREAS.

Ensure surfaces are clean, dry and free from any contaminants that may hinder adhesion. For best results; use in temperatures between 15 and 25°C. Apply to the surface holding the can approx. 25cm away. For a strong bond apply to both surfaces, for a lighter bond apply to only one. Leave the solvent content of the adhesive to evaporate for 3 - 5 minutes before bringing the surfaces and applying pressure, working outwards from the centre. Excess adhesive is easily removed by using solvent / lighter fluid etc. When finished; invert the can and spray for a few seconds in order to clear the valve ready for the next use.

**Note:** as all surfaces differ, it is recommended that this product is tested on a small area to determine

suitability before use. It is the users' responsibility to determine suitability.

### Limitations

Not recommended for use on polystyrene or plasticised PVC.

### Container Size

500ml aerosol can.

### Storage Conditions

Caution: pressurised container. Should be stored between 10 and 20°C in dry areas protected from direct sunlight. Do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame or any incandescent material. Store for up to 12 months in original unopened canister.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce can.

In the event of spillage remove all sources of ignition, ventilate the area, remove people from confined areas. Material should be mopped up immediately with an inert absorbent material such as sand.

## Specification Summary

UN1950

Flammability	Extremely flammable
Flash Point	- 40°C
Appearance	Sticky resin
Solubility in Water	Insoluble
Application Temperature	+15°C - 20°C

### Container Sizes:

<b>Code:</b>	BDA007
<b>Size:</b>	500ml
<b>Barcode:</b>	5060021361929

### Risk & Safety Phrases

R12 Extremely flammable  
R51/53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.  
R67 Vapours may cause drowsiness and dizziness.  
S2 Keep out of reach of children.  
S16 Keep away from sources of ignition - No smoking  
S23 Do not breathe vapour / spray  
S25 Avoid contact with eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S46 If swallowed, seek medical advice immediately and show this container or label. S51 Use only in well-ventilated areas

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*

### **BOND IT**

Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

