

TECHNICAL DATA	STANDARDS	Aquarelle Wall HFS	Aquarelle Wall Aquarelle Wall Borders
<b>Classification</b>			
<b>Classification</b>	EN 259	Heavy duty	
<b>Characteristics</b>			
<b>Total thickness</b>	ISO 24346 (EN 428)	0.92mm	
<b>Wear layer thickness</b>	ISO 24340 (EN 429)	0.12mm	
<b>Total weight</b>	ISO 23997 (EN 430)	1 500g/m <sup>2</sup>	
<b>Technical performances</b>			
<b>Dimensional stability</b>	ISO 23999 (EN 434)	Lengthwise: ∞ 0.80% Widthwise: ∞ 0.40%	
<b>Reaction to fire</b>	EN 13501-1	B-s2 d0 on gypsum plasterboard and on A1 or A2 substrate	C-s2 d0 on gypsum plasterboard and on A1 or A2 substrate
<b>Seam strength</b>	EN 684	≤ 150 N/50mm	
<b>Acoustical absorption</b>	NF EN ISO 354	0.05 (H)	
<b>Chemical resistance</b>	ISO 26987 (EN 423)	Good resistance	Very good resistance
<b>Hygiene</b>	—	Does not contribute to infection spreading	
<b>Form of delivery</b>			
<b>Form of delivery</b>	EN 259	Rolls: 35lm x 2m Borders: 49cm x 30-35m	Rolls: 35lm x 2m Borders: 49cm x 35m
<b>Colours</b>	—	32 + 2 borders	27 + 20 borders

The above information is subject to modifications for the benefit of further improvement (05/2014).

For more detailed technical information, please contact Tarkett.