



# BITUBOND BITUMEN PRIMER

## A Highly Penetrative, General Purpose Bitumen Primer

### Description

A highly penetrative, thin bituminous solution, black in colour.

### Uses

Use Bond It **BITUMEN PRIMER** for priming surfaces prior to the application of bituminous materials.

**BITUMEN PRIMER** can be used to prime concrete roofs and floors, cementitious screeds/renders, bitumen felt, mastic asphalt, weathered corrugated iron and steel. It is the recommended primer for use with the BITUBOND range of bituminous roof coatings, flashing tapes or mastics.

### Preparation

All surfaces must be structurally sound, clean, dry and free from surface contaminants such as grease, rust and dirt. If necessary, remove any organic growth i.e. moss or lichen, with a fungicidal wash. On bare metal a rust inhibiting product, such as red oxide or zinc phosphate should be applied and allowed to harden.

### Application

Apply by brush or spray. Using a brush, scrub the primer into the surface. Ensure that only a thin coat is applied and that there is no pooling. Alternatively, spray thinly and evenly. Priming should extend at least 75mm beyond the area to be waterproofed. Leave to dry for 2-3 hours before continuing with further work.



With fibre cement or dry rag based bituminous felts, apply generously to saturate the surface.

### Drying Time

Approximately 3-6 hours depending on drying conditions.

### Safe Handling Precautions

#### Flammability: Flammable

Keep away from sources of ignition including pilot lights and sparks (see note). Take precautionary measures against static discharge. Keep containers tightly closed when not in use. **DO NOT SMOKE**. If used in an enclosed space ensure thorough ventilation of the area (using flame proof mechanical blowers if necessary) to avoid any accumulation of vapour until the product has dried. In case of fire use dry powder, carbon dioxide (CO<sub>2</sub>), foam, sand or earth. Never use water as this may

spread the fire. **Note:** Electric motors, light/power switches and steel tools may generate sparks sufficient to ignite the product or it's vapour, resulting in an explosion and/or fire.

**Skin Contact:** Contains solvents that cause de-fatting of the skin and, in extreme circumstances, dermatitis. Avoid contact by careful working and use of a barrier cream on hands, arms and other exposed areas or wear gloves. Remove skin contamination immediately with a proprietary hand cleaner and wash with soap and water.

**Eye Contact:** Avoid contact. Could have an irritating effect. In the event of accidental contact, wash eyes immediately with clean water for 15 minutes and obtain medical attention.

**Inhalation:** Contains solvent. Stand upwind of the work to avoid inhalation. Switch off all working ventilation inlets prior to using the material; leave covered until there is no odour of the solvent in the vicinity. In the event of discomfort as a result of inhalation move person to fresh air. If discomfort persists seek medical advice.

**Oral Ingestion:** With proper handling this should not occur. The possibility can be minimised by not consuming food in the working environment and by washing hands thoroughly before eating, drinking or smoking.

**Spillage:** Spilt material should be mopped up immediately with an inert absorbent material, such as sand, and disposed of in accordance with regulations.

**Disposal of Containers:** Do not leave containers on site where residue could be a hazard to children, animals or the environment. Replace lids securely and remove any containers to a central disposal point.

### Limitations

- Do not use in areas where subsequent solvent contact is likely.
- Do not use for potable drinking water tanks.
- Allow sufficient drying time between coats.
- Bitumen Paint may bleed through any paints subsequently applied over it. Apply a primer recommended by the paint manufacturer before overpainting.

### Cleaning Of Tools

Clean with paraffin (kerosene) or white spirit.

### Storage Conditions

Store under cover away from sources of heat and ignition. Keep containers sealed when not in use.

### Storage Life

Shelf life of this product is a minimum of 5 years under good storage conditions in original unopened containers.

## Specification Summary

Type of solvent	White Spirit
Approximate Flashpoint Test Method BS2000:Part 170:1982 [IP170/75 (81)]	40°C
Approximate Specific Gravity	0.90
Approximate Coverage	4-6m <sup>2</sup> per 1 litre (dependant on substrate porosity)
Application Temperature Limits	Normally 5°C to 35°C and free from ice/ water

### Container Sizes:

<b>Size:</b>	1 Litre	2.5 Litre	5 Litre	25 Litre
<b>Code:</b>	BDB034	BDB019	BDB020	BDB040
<b>Barcode:</b>	5060021363626	5060021362360	5060021362377	5060021363602

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number: 6152  
ISO 9001  
ISO 14001



**BOND IT**  
Unit G16 River Bank Way, Lowfields Business Park, Elland, West  
Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310



V3 12/01/16  
Supersedes V2 22/3/12