



Never compromise on quality!



Drive Alive
revive your drive...

DRIVE ALIVE CLEAR COAT BLOCK SEALER

Description

A ready-to-use, clear sealant for block paving, paths and driveways.

- **Protects from water penetration; staining and dirt/grime build-up.**
- **Advanced "Hybrid" technology.**
- **Ready to use.**
- **Excellent abrasion and chemical resistance.**
- **Inhibits organic growth.**
- **Solvent free.**

Uses

Designed to protect from water penetration, oil or grease spillages and dirt/grime build-up. Will enhance present colour and extend the lifespan of the treated surface.

Benefits:

- Solvent-free formulation - low odour.
- Facilitates easier cleaning.
- Improves water resistance and UV resistance.
- Contains fungicide which retards mould growth.

Preparation

Remove any moss or lichen that may be present. For best results use DRIVE ALIVE ORGANIC CLEANER prior to application (ensure the residue is thoroughly washed off and left to dry for 48 hours prior to application.) Ensure the surface to be treated is free from oil, grease, dust and any other loose material that may hinder adhesion. It is recommended that a test be carried out on a small inconspicuous area to ensure the required effect is achieved.

Application

DRIVE ALIVE CLEAR COAT BLOCK SEALER is ready to use, and does not require diluting. We advise that you test this product on a small inconspicuous area prior to use to check compatibility. **STIR WELL BEFORE USE.** Ensure that the surface is completely dry. Apply a single coat using either a brush, roller or squeegee, ensuring no pooling or ponding occurs.

Allow 3-4 hours drying time before trafficking the area. Application temperature between 5°C and 30°C. Colder humid conditions will slow drying times.

Limitations

Do not apply to wet or damp surfaces or in conditions of high humidity. Surfaces should be allowed to dry completely for 48 hours prior to application. Do not use if rain is imminent (protect from rain until dry). Do not apply to non-porous surfaces. Keep children and animals away and do not traffic until fully cured. Do not allow any run off to contaminate drains, waterways or plants. Do not use in temperatures below +5°C and above +30°C.

Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

Shelf Life

24 months when stored according to manufacturers instructions.

Coverage

One 4 Litre container will cover approximately 40 - 60m² for a single coat depending on surface porosity.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Product presents a low hazard in correct use.
- ◆ Avoid eye contact. In the event of contact irrigate eyes immediately with plenty of cold, clean water for 15 minutes and seek medical attention.
- ◆ Do not ingest. In the event of ingestion, do not induce vomiting, drink plenty of water and seek medical attention.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.

- ◆ Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- ◆ See separate material safety data sheet for full handling, use and storage.

Note:

It is necessary to seal pavements prior to the application of any pointing or jointing compound. Some compounds have the capability of staining porous paving materials. Ensure **CLEAR COAT** has completely cured prior to pointing. Do not apply

CLEAR COAT to any uncured wet pointing or to any dry mix cement compound. If applying **CLEAR COAT** to new pavements ensure a sufficient period of weathering (as recommended by the paving manufacturer) has elapsed in order to avoid efflorescence. Pavements can be resealed using a single coat of **CLEAR COAT** at 3 to 4 year intervals. The surface may still be sealed even when the surface tension appears to have reduced. Apply to a small test area and check a few days later. Avoid over application.

SPECIFICATION SUMMARY

Physical Properties	Milky white liquid, non flammable, zero VOC, water miscible.
Application:	STIR WELL BEFORE USE. Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	5°C to 30°C
Drying Time	1-2 hours in warm, sunny conditions
Coverage Rate	40 - 60m ² per 4 litre container
Cleaning	Rinse then wash brushes and rollers in warm, soapy water
Shelf Life	2 years

Container Sizes

Code:	BDCCBS4
Size:	4L
Barcode:	5060021368300

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.

BOND IT

Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 11/6/12



Certificate Number: 6152
ISO 9001
ISO 14001

