



Never compromise on quality!

Published: June 2011

INSTANT POT HOLE REPAIRER

Description

A cold lay asphalt concrete pot hole repair compound.

Features & Benefits

- Used in wet, freezing and hot conditions.
- No special preparation required.
- Instant trafficking.
- Recyclable packaging.
- Compatible with flexible road surfaces.
- Solvent free.
- Ready to use – No need to add water.
- Polished stone value 60 psv.
- Absolutely no waste.
- Environmentally friendly – No CO₂ gases.

Uses

A suitable solution for roads, pavements, driveways and car parks. The product can be trafficked instantly in wet, freezing and hot conditions and at the same time is compatible with the existing road surface. **PERMANENT POT HOLE REPAIRER** can be applied at depths up to 100mm. (Greater depths can be achieved by applying the layer-on-layer method).

Application

PERMANENT POT HOLE REPAIRER has high skid resistance due to the specially formulated bitumen and interlocking aggregate. It is supplied in 25Kg containers.

Pot hole repairs can be achieved at any depth.

1. Ensure pothole is free of debris and standing water.
2. Fill the pothole straight from the tub.
3. Apply slightly proud of the pothole.
4. Tamp down to compact material to complete the application.

Storage Conditions

Store in a cool and well-ventilated place.

Shelf Life

In correct conditions for sealed goods is 6 months.

Size:

25Kg tubs.

Coverage

1m² x 15mm (compacted).

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Ensure that protective gloves, overalls and protective footwear are worn at all times while handling the material. Avoid skin contact. However, should the bitumen binder adhere to the skin it can be removed with soap and water. Seek medical advice if discomfort continues. If product comes into contact with the eyes rinse with plenty of water and seek medical advice. Material Safety Data Sheet available for the professional user upon request. It is the users' responsibility to determine suitability for use. A test on a small inconspicuous area is recommended prior to use. Please refer to technical data sheet for more in depth information regarding application and coverage.

Specification Summary

Appearance	Black aggregate
Solubility In Water	Non soluble
Flammability	Non flammable

Container Sizes

Code:	BDPHR25
Size:	25Kg
Barcode:	5060021369093

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.

BOND IT
Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

