

POWER TONE 3 IN 1 Concentrated Cement Toner

Description

A premium quality, concentrated cement dye designed to ensure a uniformed colour is attained when colouring cement and mortar. Conforms to BS1014.

Bond It POWER TONE also contains plasticising and waterproofing agents which eliminates the need for additional admixtures. Use of POWER TONE also reduces efflourescence.

Benefits

- Permanently colours cement/mortar.
- Reduces efflorescence.
- Non fading.
- Integral part of mortar or concrete.
- Versatile and cost-effective.
- Saves time and money.
- Guaranteed pre-measured dosage.
- Controlled dosage to ensure uniformity.
- Free of dust for easier and healthy handling.
- Less wastage.

Uses

As a liquid colourant for all cement based mixes ie. cement, render, mortar, etc, with the added benefit of containing waterproofing and plasticising ingredients.

Application

This product is supplied in a carefully measured dosage bottle, simply squeeze the bottle to administer the correct amount of liquid into the delivery nozzle.

Use at the rate of 50-500ml per 25Kg bag of cement. Add **POWER TONE** to the sand/cement mix - as a guide a maximum of 1L per 25 kg of cement is recommended.

Choice and depth of colour is dependant on the dosage used. Add water slowly to obtain the desired consistency, when mixing by hand ensure thorough mixing to achieve maximum plasticity. Uniformity of colour can be ensured by using constant water and constant mixing time.

Do not use at temperatures below $+2^{\circ}C$ or when temperature is expected to drop below $0^{\circ}C$ within 24 hours.

Coverage

1L will be sufficient for up to 20 bags of 25kg cement.

Storage Conditions

Store in cool, dry conditions.

Shelf Life

Up to 24 months when stored according to manufacturers instructions.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- Irritant.
- Avoid eye contact, wear eye and face protection.
 In the event of contact irrigate eyes immediately with plenty of cold, clean water for 15 minutes and seek medical attention. Could cause irritation.
- Avoid prolonged contact with skin. Wear wellington boots, protective clothing and gloves. Could cause irritation.
- Do not ingest. In the event of ingestion, do not induce vomiting, drink plenty of water and seek medical attention.
- Thoroughly wash hands with soap and water after use.
- Keep out of reach of children.
- Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- See separate material safety data sheet for full handling, use and storage.

Specification Summary

Specific Gravity	approx 1.5
Flammability	Non Flammable
ph	12-14
Composition	Viscous liquid
Freeze Point	0°C
Chloride Content	<0.01%
Conforms to:	BS1014

Container Sizes

Code:	BDH065R	BDH065BL
Colour:	Red	Black
Size:	1L	1L

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.

BOND IT

