Fortessa[™]

Laydex Ltd Unit 3 Allied Industrial Estate Kylemore Rd , Dublin 10

Tel: 01 6426600

OVERHEAD DOOR CLOSER - SIZE 3

Product Overview:

A fixed power overhead door closer suitable for light and medium duty and general applications including student accommodation, flat entrance doors etc.



Testing & Standards:

- CE marked against EN1154
- Included in successful fire test to EN1634
- Suitable for use on timber fire doors of up to 120 minutes fire resistance
- Safe in use
- High corrosion resistance

Specification

| Closing Force | EN Size | 3 |
|------------------------------|---------------------|------|
| Door Size (max) | Width (mm) | 950 |
| | Weight (kg) | 60 |
| Body Dimensions | Length (mm) | 180 |
| | Width (mm) | 42 |
| | Depth (mm) | 64 |
| Application | Regular Fig. 1 | У |
| | Parallel Arm Fig. 6 | У |
| | Transom Fig. 61 | у |
| Mechanism | Rack & Pinion | У |
| Power Shoe Bracket | | У |
| Angle Of Opening | | 180° |
| Non Handed | | у |
| Power Adjustment by Spring | | n |
| Power Adjustment by Position | | n |
| Adjustable Sweep Speed | | у |
| Adjustable Latch Speed | | у |
| Adjustable Backcheck | | n |
| Adjustable Delayed Action | | n |
| Guarantee | Years | -10 |
| | | |



Options

| Architave Brackets | n |
|--|---|
| Drop Plates | n |
| Hold-Open Arm (not suitable for use on fire doors) | n |
| Slide Arm & Track | n |
| Hollow Door Fixing Pack | n |
| Saddle Bracket For Glass Door Installation | n |
| | |

Cover Options

| Radius Edge | n |
|-------------|---|
| Semi-Radius | n |
| Full-Radius | n |
| Square | n |

Finish Options

| No Cover | | SE, GE |
|----------|--|--------|
| Cover | | n |

