



Never compromise on quality!

Published: September 2002

SILICONE RELEASE SPRAY

Lubricating Oil

Description

A silicone lubricating oil in an aerosol can.

Uses

Bond It **SILICONE RELEASE SPRAY** can be used for conveyors in the food and drink industry where a food safe non emulsifying lubricant is required. The moulding industry to improve productivity and ease of release. Textile industry where a clean non staining lubricant is required. Automotive to prevent door gaskets sticking and interior trim squeaks. This product will not attack painted surfaces or plastics.

Application

Spray in short bursts on to the surfaces that require lubrication, wipe away excess with a soft cloth.

For mould release applications remove any material from the mould, spray uniformly paying particular attention to corners and areas of fine detail. Ensure all surfaces have received a coating, the silicone can be gently spread using a soft non woven cloth. Best results will always be achieved from moulds with smooth unpitted finishes.

Limitations

Do not use on surfaces to be painted as silicone may induce surface irregularities in the paint. For polystyrene, first spray the release onto a cloth and apply by hand to protect the polystyrene from the propellant.

Storage Conditions

Store below 50°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Observe the label precautions. **SILICONE RELEASE SPRAY** must be stored in accordance with the flammable liquid storage regulations.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce canister.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

Health & Safety

- ◆ Highly flammable - remove all sources of ignition. Do not smoke. Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupation exposure limits. Use only in areas from which all sources of heat, sparks and open flame have been excluded
- ◆ Avoid eye contact. In the event of contact wash with running water for 15 minutes and seek medical attention. Wear goggles.
- ◆ Ensure good ventilation - harmful by inhalation. Do not induce vomiting. Wear vapour protection mask.
- ◆ Avoid prolonged contact with skin. Wear gloves.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Appearance	Colourless oil
Flammability	Highly Flammable
Flash Point	-40°C
Boiling Point	35°C
pH	N/A
Solubility in Water	Insoluble

Container Sizes:

Code:	BISR500
Size:	500ml

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.

