



Never compromise on quality!

Published: May 2007

MULTI-PURPOSE SPRAY LUBRICANT

Description

A low viscosity solvent and oil blend giving excellent penetrating, de-watering and lubricating properties. Supplied in 200ml aerosol cans with a straw for accurate dispensing.

Uses

MULTI-PURPOSE SPRAY LUBRICANT is a high performance, multi-application fluid which has excellent anti-corrosive properties. It can be used for a wide range of demanding uses for automotive and general engineering.

Suitable for freeing seized fasteners particularly where corrosion is a problem. Also as a general purpose lubricant and cleaner to free tight linkages. Displaces moisture and condensation from material surfaces. Light duty lubricant which can be directed towards hard to access components.

Preparation

Ensure surfaces are clean, dry and grease and oil free.

Application

Attach the straw to the nozzle and aim at the component, keeping the can upright. For seized parts allow to penetrate from all angles for some seconds and progressively loosen adding more lubricant as the threads free.

For stiff linkages remove old grease or dirt and direct the jet onto the linkage until free of old build up, activate linkage to allow full penetration. Reseal with fresh grease for heavy duty applications.

To displace moisture wipe away excess then spray a light coat across all surfaces. Do not spray at hot surfaces or live electrical systems.

Storage Conditions

Store below 50°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Observe the label precautions. **MULTI-PURPOSE SPRAY LUBRICANT** must be stored in accordance with the flammable liquid storage regulations.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce canister.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

Health & Safety

- ◆ Highly flammable - remove all sources of ignition. Do not smoke. Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupation exposure limits. Use only in areas from which all sources of heat, sparks and open flame have been excluded
- ◆ Avoid eye contact. In the event of contact wash with running water for 15 minutes and seek medical attention. Wear goggles.
- ◆ Ensure good ventilation - harmful by inhalation. Do not induce vomiting. Wear vapour protection mask.
- ◆ Avoid prolonged contact with skin. Wear gloves.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Flammability	Highly Flammable
Flash Point	-40°C
Boiling Point	140°C
pH	N/A
Solubility in Water	Insoluble

Container Sizes:

Code:	BIMP200	BIMP400
Size:	200ml	400ml

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.

