

Specification

Modular heterogeneous product with interlocking connection.


Product standard: ISO 10582.

CERTIFICATION & CLASSIFICATION	STANDARDS	Tilt
Type of floor covering	EN ISO 10582	Modular heterogeneous product with interlocking connection
CE certification	EN 14041	Yes
Classification	EN ISO 10874 - EN 685	Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS	STANDARDS	Tilt
Total thickness	EN ISO 24346 - EN 428	5.0 mm
Wear layer thickness	EN ISO 24340 - EN 429	0.70 mm
Surface treatment (PUR)		Yes
Total weight	EN ISO 23997 - EN 430	7400 g/m ²
Wear layer binder content	ISO 10582	Type I
Form of delivery	EN ISO 24342 - EN 427	
	Tiles	91.44 x 91.44 cm (Granite) 3 tiles/box (= 2.51 m ² - 20.10 kg)
		45.72 x 45.72 cm (Concrete) 10 tiles/box (= 2.09 m ² - 16.70 kg)
TECHNICAL PERFORMANCES	STANDARDS	Tilt
Dimensional stability	EN ISO 23999 - EN 434	< 0.15 %
Reaction to fire	EN 13501-1	B _{fl} -s1 over concrete substrate
Residual indentation	EN ISO 24343-1 - EN 433	< 0.10 mm
Furniture leg	ISO 16581 - EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curl resultant to heat	ISO 23999 - EN 434	≤ 2 mm
Thermal resistance	EN ISO 10456	approx. 0.05 m ² K/W
Impact sound reduction	EN ISO 717-2	ΔL _w = 6 dB
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987 - EN 423	Resistance
Slip resistance	EN 13893 DIN 51130	μ ≥ 0.30 DS R9
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 109 Ω
Colours		Granit: 4 - Concrete: 3

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF: 482050000000F



The 2 formats are not interconnectable

