

Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: TREMCO CP151

· MSDS code: W-T-CP151

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the mixture Primer / Subcoating
- · Uses advised against Not suitable for use on non-ferrous metals.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

tremco illbruck Coatings Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R37/38: Irritating to respiratory system and skin.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

F; Highly flammable

R11: Highly flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Contains:

methyl methacrylate ethylene dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves. P261 Avoid breathing vapours.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 80-62-6	methyl methacrylate	50- <75%
EINECS: 201-297-1	Xi R37/38; Xi R43; F R11	
Reg.nr.: 01-2119452498-28-xxxx	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 97-90-5	ethylene dimethacrylate	1- <5%
EINECS: 202-617-2	Xi R37; Xi R43	
Reg.nr.: 01-2119965172-38-xxxx	Skin Sens. 1, H317; STOT SE 3, H335	

• Additional information: For the wording of the listed risk phrases refer to section 16.

-GB



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove from the skin using a cloth or paper. Then clean with water and soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Irritating to respiratory system.

Irritant to skin and mucous membranes.

Allergic reactions

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Fumes can combine with air to form an explosive mixture.

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective clothing.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

(Contd. on page 4)



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Do not breathe vapour.

Open and handle receptacle with care.

Keep away from heat and direct sunlight.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Highly flammable.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Storage temperature: +12 \circ to +25 \circ

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

Additional information:

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

(Contd. on page 5)



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

· Respiratory protection:

Use only in well-ventilated areas.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

· Protection of hands:



Protective gloves

· Material of gloves

Butyl rubber, BR

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Colourless
Odour: Strong

· Odour threshold: 0.05 ppm (CAS 80-62-6)

Melting point/Melting range: -48 ℃

· Boiling point/Boiling range: 100 ℃ (CAS 80-62-6)

• Flash point: 11 $^{\circ}$ (CAS 80-62-6)

(Contd. on page 6)





Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

	(Contd. of page 5)	
· Ignition temperature:	430 ℃ (CAS 80-62-6)	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	2.1 Vol % (CAS 80-62-6) 12.5 Vol % (CAS 80-62-6)	
· Vapour pressure at 20 ℃:	38.7 mBar (CAS 80-62-6)	
· Density at 20 ℃:	0.99 g/cm ³	
· Solubility in / Miscibility with water at 20 ℃:	15.9 g/l (CAS 80-62-6)	
· Partition coefficient (n-octanol/water): 1.38 log POW (CAS 80-62-6)		
· Viscosity: Dynamic at 20 ℃:	100 - 130 mPas	
Solvent content:VOC (EU)9.2 Other information	not applicable No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with heavy metals.

Reacts with acids, alkalis and oxidizing agents.

Reacts with amines.

Reacts with peroxides and other radical forming substances.

Exothermic polymerization.

· 10.4 Conditions to avoid

Water / moisture.

Keep away from heat.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

	· LD/LC50 values relevant for classification:	
Ī	80-62-6 methyl methacrylate	
Ī	Oral LD50 7872 mg/kg (rat)	

(Contd. on page 7)



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 6)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Disposal must be made according to official regulations.

Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

· Waste disposal key: UK: H3A H4

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

· Uncleaned packaging:

· Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Non contaminated packagings may be recycled.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, ADN, IMDG, IATA

UN1866

(Contd. on page 8)



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

	(Contd. of page 7)
· 14.2 UN proper shipping name	(SS.N.S. OI page 1)
· ADR	1866 RESIN SOLUTION, mixture
· IMDG, IATA	RESIN SOLUTION, mixture
· 14.3 Transport hazard class(es)	
· ADR	
Class	3 (F1) Flammable liquids.
· Label · ADN/R Class:	3
	3
· IMDG, IATA	
· Class · Label	3 Flammable liquids.3
· 14.4 Packing group · ADR, IMDG, IATA	II
14.5 Environmental hazards:Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):EMS Number:	339 F-E,S-D
• 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L Code: F2
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
. Transport category	Maximum net quantity per outer packaging: 500 ml 2
Transport categoryTunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
	(Contd. on page 9)

____ GB -



Printing date 12.08.2014 Version number 2 Revision: 12.08.2014

Trade name: TREMCO CP151

(Contd. of page 8)

· UN "Model Regulation":

UN1866, RESIN SOLUTION, mixture, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC.

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

- · National regulations:
- Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

R11 Highly flammable.

R37 Irritating to respiratory system.

R37/38 Irritating to respiratory system and skin.

R43 May cause sensitisation by skin contact.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.

GB