

## Specification

Modular vinyl floor covering, with glass fibre reinforcement. TopClean XP™ polyurethane reinforcement.  
 In plank and tile format.

Product standard: EN ISO 10582.

CERTIFICATION & CLASSIFICATION	STANDARDS	iD Inspiration Loose-lay
Type of floor covering	EN ISO 10582	Compact resilient floor covering
CE certification	EN 14041	Yes
Classification	EN ISO 10874	Commercial: 33 Industrial: 42
TECHNICAL CHARACTERISTICS	STANDARDS	iD Inspiration Loose-lay
Total thickness	EN ISO 24346	4.5 mm
Wear layer thickness	EN ISO 24340	0.55 mm
Surface treatment (PUR)		Yes
Bevelled edges		No
Total weight	EN ISO 23997	7500 g/m <sup>2</sup>
Wear layer binder content	ISO 10582	Type I
Form of delivery	EN ISO 24342 Planks	22.9 x 121.9 cm 10 planks/box (= 2.79 m <sup>2</sup> - 20.9 kg) 52 boxes/pallet (= 145.16 m <sup>2</sup> - 1088.7 kg)
	Tiles	30.5 x 61 cm 14 tiles/box (= 2.6 m <sup>2</sup> - 19.5 kg) 54 boxes/pallet (= 140.65 m <sup>2</sup> - 1054.9 kg)
TECHNICAL PERFORMANCES	STANDARDS	iD Inspiration Loose-lay
Dimensional stability	EN ISO 23999	≤ 0.10 %
Reaction to fire	EN 13501-1	B <sub>f1</sub> s1
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Furniture leg	EN 424	No damage
Castor chair	EN ISO 4918	No damage
Thermal resistance	ISO 10456	0.04 m <sup>2</sup> K/W
Impact sound reduction	EN ISO 717-2	8 dB
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987	High resistance
Slip resistance	EN 13893 DIN 51130	μ ≥ 0.30 DS R9
Electrical properties	EN 1081	ca. 10 <sup>11</sup> Ohm
Colours		22

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

CUSTOMS TARIFF: 482050000000F

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

