

Specification

Loose lay printed acoustic floorcovering in tile format. Glass fibre reinforcement. TopClean XP™ Polyurethane reinforcement on surface.

CERTIFICATION & CLASSIFICATION	STANDARDS	iD Square
Floor covering classification	EN ISO 10874	Acoustic resilient floor covering Commercial very heavy: 34
CE certification	EN 14041	Yes
TECHNICAL CHARACTERISTICS	STANDARDS	iD Square
Total thickness	EN ISO 24346	4.5 mm
Wear layer thickness	EN ISO 24340	0.80 mm
Total weight	EN ISO 23997	5195 g/m ²
Wear layer binder content	ISO 10582	Type I
Form of delivery	EN ISO 24342	
	Planks	25 x 100 cm 9 planks/box (= 2.25 m ² - 12 kg) - 48 boxes/pallet
	Tiles	50 x 50 cm 9 tiles/box (= 2.25 m ² - 12 kg) - 48 boxes/pallet 66 x 66 cm 5 tiles/box (= 2.22 m ² - 12 kg) - 26 boxes/pallet
TECHNICAL PERFORMANCES	STANDARDS	iD Square
Dimensional stability	EN ISO 23999	≤ 0.10 %
Reaction to fire	EN 13501-1	B _{f1} s1 loose-laid or glued over any A2 _{f1} or A1 _{f1} substrate (concrete) C _{f1} s1 loose-laid or glued over any derivate wood substrate
Residual indentation	Average measured value EN ISO 24343-1 requirement	0.15 mm ≤ 0.20 mm
Furniture leg	EN 424	No damage
Castor chair	EN ISO 4918	No damage
Thermal resistance	ISO 10456	0.04 m ² K/W
Impact sound reduction	EN ISO 717-2	ΔL _w = 15 dB (±1 dB)
Reduction of in room impact noise	NFS S 31-074	Class B - L _{n,e,w} = < 75 dB
Acoustical absorption	EN ISO 11654	α _W = 0.05
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987	High resistance
Slip resistance	EN 13893 DIN 51130	μ ≥ 0.30 R9
Electrical properties	EN 1081	R _i > 10 ¹⁰ Ohm
Colours		41

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF : 482050000000F

