

SELF ADHESIVE SCRIM TAPE Drywall Joint Tape

Description

A fibreglass mesh tape giving increased strength and extra reinforcement for joining plasterboard.

Benefits

- Eliminates need for pre-plastering.
- Saves time and money.
- Self adhesive.
- Use with a setting type compound.
- Eliminates blisters and bubbles.

Coverage

BDDJ2: 90 metre roll x 2 inches. BDDJ3: 90 metre roll x 3 inches. BDDJ4: 45 metre roll x 4 inches.



Application

Nominal Values

		METRIC	IMPERIAL	ASTM METHOD
Construction: (per 10cm - per inch)	Warp Weft	36 36	9 9	D-3775
Weight: (g/m ² - oz/yd ²)		62.7+/- 2.7	1.85 +/- 0.1	D-3776
DPU (Coating and PSA on fabric in weight %)		40-45%	40-45%	SGTF
Thickness: (per mm - per inch)		0.3	0.01	D-1777
Tensile Strength: (N/2.54cm - ibs/in)	Warp Weft	222 467	50 105	

Weave Type: Non Interlaced Fibreglass Technology (NIFt).

All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our product are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind express or implied is made or intended. Value presented above are nominal and only to be used as guidelines.

Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN. Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



