



Never compromise on quality!



# FIX 'N' GROUT TILE ADHESIVE

## Premium Grade Ceramic Tile Adhesive & Grout

### Description

A premium grade fungal resistant brilliant white waterproof ceramic tile adhesive and grout conforming to EN 12004:2007 Type D, Class 2. designed to permanently fix and grout ceramic wall tiles in areas subject to prolonged damp conditions.

### Uses

Bond It **FIX 'N' GROUT TILE ADHESIVE** is a brilliant white water resistant wall tile adhesive and grout ideal for fixing and grouting tiles in kitchens, bathrooms, toilets and showers.

This ready to use adhesive and grout is suitable for use on:

- ◆ gypsum plaster
- ◆ concrete render
- ◆ brick
- ◆ plywood
- ◆ blockboard
- ◆ fibre cement sheet
- ◆ glazed tiles
- ◆ most common building materials.

### Preparation

Ensure all surfaces are dry and free from dirt and any other contaminants that may hinder adhesion. New plaster should be allowed to thoroughly dry out for a minimum of 4 weeks and primed with Bond It PRIMER & FLEXIBLE ADMIXTURE prior to application. Existing plaster should have any holes or cracks filled and be primed where necessary, and timber should be sealed with Bond It PRIMER & FLEXIBLE ADMIXTURE prior to application.

### Application

Apply the adhesive using a 6mm notched trowel to a depth of 3mm with the ribs running horizontally, and only working with an area that can be completed within 15 minutes (approximately 1m<sup>2</sup>). Tiling can either take place from the top or bottom depending on application by pressing the tile firmly into the adhesive with a twisting action, and leaving a 1-2mm space around each tile. Any adhesive on the front of the tile should be removed with a damp cloth immediately and the tiles left for 4-8 hours prior to grouting.

For tiles larger than 250 x 300mm a cement based powder adhesive, such as Bond It CTA, should be used.

### Limitations

Bond It **FIX 'N' GROUT TILE ADHESIVE** is not recommended for use on floors or areas subject to continuous water immersion e.g. swimming pools, ponds and external use, or for use where the ambient temperature is below 5°C. **Note: May cause discolouration of some types of marble.**

### Storage Conditions

Store in cool, dry conditions between a temperature of 2°C and 30°C. PROTECT FROM FROST.

### Shelf Life

Minimum 12 months.

### Coverage

Approximately 2-3Kg/m<sup>2</sup> per litre for tiling  
5Kg/m<sup>2</sup> per litre for grouting

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

- ◆ Low hazard product - safe in normal use.
- ◆ Avoid eye contact.
- ◆ Avoid prolonged contact with skin.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs