

CERTIFICATION SERVICES

BTTG Ref No: 51/00459

Certificate of conformity of the factory production control,

0338-CPR-0911

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Protect&Drain

Product parameters:

For details of product parameters, see Annex 1

Product description:

Geotextiles

Intended uses:

for drainage systems (D)

produced by or for
Visqueen Building Products Limited
Heanor Gate Road
Heanor
Derbyshire
DE75 7RG

Factory code FLS101RZ

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 13252:2000/A1:2005

under system 2+ are applied and that

the factory production control fulfils all the prescribed requirements set out above.

This certificate was first issued on 14th October 2013 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Signed for and on behalf of BTTG

Mike Nunney
Operational Head, Certification
BTTG
Leeds, 14 October 2013

For terms and conditions of issue, see the final page.



Page 1 of 3

BTTG Ltd. Registered Office: Wira House, West Park Ring Road, Leeds. LS16 6QL. United Kingdom Registered in England No. 4628697

Tel: +44 (0)113 259 1999 Fax: +44 (0)113 278 0306 e-mail: info@bttg.co.uk

51/00459

Annex 1

0338-CPR-0911

This annex lists details of the product parameters as provided by the producer in their Declaration of Performance.

Protect&Drain

Essential characteristics
Tensile Strength
Tensile Elongation
Water Permeability

Durability

Test Method

EN ISO 10319 EN ISO 10319 EN ISO 11058 Performance

MD 12kN/m (-1.2kNm) CMD 12kN/m (-1.2kNm) MD 20% (±10%) CMD 20% (±10%) 1.83 l/m/s² (-0.46 l/m/s²)

To be covered within two weeks after installation.

Predicted to be durable for more than 25 years in soils with a pH between 4 and 9 on the basis of a durability assessment.



Page 2 of 3 51/00459

<u>Terms and Conditions associated with the issue of</u> <u>Certificate of conformity of the factory production control No: 0338-CPR-0911</u>

- 1. This certificate is issued subject to BTTG's standard terms of business.
- 2. Any change to the product and/or technical specification shall be immediately notified to BTTG.
- 3. The Manufacturer / Authorised Representative shall have continuous surveillance of Factory Production Control carried out by a Notified Body and a re-assessment of Factory Production Control every three years.
- 4. This certificate remains the property of BTTG and will be withdrawn if any of the conditions attached to its issue are not complied with.
- 5. Marking and instructions have been assessed in the English language only. It is the Manufacturers/Authorised Representatives responsibility to obtain and supply language versions acceptable to the country where the product is to be sold.
- 6. This certificate remains valid only if satisfactory maintenance of independent certification against ISO 9001 is achieved.